

OL1 Low Intensity Obstruction Light

FAA Type L-810 Red Incandescent



Overview

The TWR OL1 is an FAA Type L-810 low intensity red obstruction light with an incandescent bulb and a painted cast aluminum base.

Key Features

- 2-Year limited warranty
- Available in side hub or bottom hub configurations
- No special tools required for installation or maintenance
- Cast aluminum base, stainless steel latches and hardware for corrosion protection
- High quality porcelain receptacle
- Neoprene gasket for weather proofing
- Stainless steel safety cable

General Specifications	
Light Source	(1) Incandescent Bulb
Lens Material	Fresnel Pyrex Glass
Base Material	Cast A356 Aluminum
Power Requirements	120 - 240 VAC 50 - 60 Hz or 12-24 VDC
Power Consumption	116 Watts
Operating Temperature Range	-67°F to +130°F (-55°C to +55°C)
Effective Intensity (Night)	32.5 CD Minimum
Lamp Current	1 Amp
Vertical Beam	10° Minimum
Horizontal Coverage	360°
Wind Load	CAAA 0.5 ft ²
Height	7.5 in. (19.05 cm)
Diameter	4.875 in. (12.38 cm)
Weight	2.45 lbs. (1.11 kg)
Hub Sizes	0.75 in. (1 in. or 1.25 in. with enlarger)

