

10810 W LITTLE YORK RD. STE 130- HOUSTON TX 77041-4051

VOICE: 713-973-6905 - FAX: 713-973-9352

web: [www.twrlighting.com](http://www.twrlighting.com)

## IMPORTANT!!!

PLEASE TAKE THE TIME TO FILL OUT THE FORM COMPLETELY. FILE IN A SAFE PLACE. IN THE EVENT YOU EXPERIENCE PROBLEMS WITH OR HAVE QUESTIONS CONCERNING YOUR CONTROLLER, THE FOLLOWING INFORMATION IS NECESSARY TO OBTAIN PROPER SERVICE AND PARTS.

**MODEL #** LC-STAR (Lighting Controller - Star)

**SERIAL #** \_\_\_\_\_

**PURCHASE DATE** \_\_\_\_\_

**PURCHASED FROM** \_\_\_\_\_





THIS PAGE IS INTENTIONALLY LEFT BLANK



Questions or information beyond this manual, please contact TWR Lighting, Inc.

TWR Lighting, Inc.  
10810 W Little York Rd. Ste 130- Houston, TX 77041-4051  
Voice: **713-973-6905** - Fax: **713-973-9352** – Toll Free: **800-661-8606**  
E-mail: [techsupport@twrlighting.com](mailto:techsupport@twrlighting.com)  
web: [www.twrlighting.com](http://www.twrlighting.com)

**The use of Non-original manufacturer parts which are not approved by TWR Lighting, Inc. may invalidate the warranty as well as compliance with requirements as published in the FAA Advisory Circulars AC70/7460-1L, AC150/5345-43J and AC150/5345-53 and ICAO Annex 14 Volume 2 standards.**

#### **DISCLAIMER**

While every effort has been made to provide a complete, up-to-date, accurate manual, no liability claims for damages resulting from any errors or omissions in this manual will be accepted by TWR Lighting, Inc.

#### **COPYRIGHT**

Copyright © 2005 TWR Lighting, Inc.

All rights reserved. Reproduction or use of any part of this installation & operation manual is prohibited without express written permission from TWR Lighting, Inc.



## Contents

1	GENERAL INFORMATION .....	6
1.1	Monitoring: Customer Failure Alarm - Dry contact closure (Form C) .....	6
1.1.1	Power fail.....	6
1.1.2	Beacon White fail .....	6
1.1.3	Beacon Red fail .....	6
1.1.4	Mode State Status .....	6
1.1.5	Photocell fail.....	6
1.1.6	Sidelight fail .....	6
1.1.7	Communications fail.....	7
1.2	User Interface functions.....	7
1.2.1	Ethernet/WIFI.....	7
1.2.2	Photocell override .....	7
2	INSTALLATION .....	7
2.1	STAR CONTROLLER (Part # LC-STAR) .....	7
2.1.1	Controller mounting .....	7
2.1.2	Controller electrical .....	7
2.1.3	Controller cable for light operation.....	7
2.1.4	Controller sidelight sensor .....	8
2.1.5	Controller alarm monitoring connections .....	8
2.1.6	Controller external photocell (optional).....	8
2.1.7	Controller wireless monitoring modem (optional).....	8
2.2	BEACON LIGHT (Part # LONESTAR).....	8
2.2.1	Beacon mounting .....	8
2.2.2	Beacon electrical .....	8
2.3	SIDELIGHT (Part # OL1xxxx).....	8
2.3.1	Sidelight mounting .....	8
2.4	CABLE (Part # LCABLE-1) .....	9
2.4.1	Cable specifications .....	9
2.4.2	Cable mounting .....	9
2.4.3	Cable connection .....	9
3	Operation .....	9
3.1	LIGHTING SYSTEM COMMISSIONING .....	9
3.1.1	COMMISSIONING FORM .....	9
3.1.2	IMPEDANCE CHECK .....	11
3.2	STAR CONTROLLER (Part # LC-STAR) .....	12
3.2.1	Screen and Controls .....	12



3.2.2	PCB LED Indicators.....	31
3.3	BEACON LIGHT (Part # LONESTAR).....	32
3.3.1	Beacon power.....	32
4	Maintenance .....	32
4.1	TROUBLESHOOTING .....	32
4.1.1	STAR CONTROLLER (Part # LC-STAR) .....	32
4.1.2	BEACON LIGHT (Part # LONESTAR).....	34
5	MAJOR COMPONENTS PARTS LIST.....	35
6	WARRANTY AND RETURN POLICY .....	36
6.1	RMA FORM.....	39
7	CONTROLLER CHASSIS LAYOUT .....	40
8	CONTROLLER SCHEMATIC .....	40
9	SIDELIGHT MODULE DETAILS .....	40
10	LIGHTING KITS .....	40
11	LONESTAR BEACON DETAIL.....	40
12	SIDELIGHT L810 DETAIL.....	40
13	JUNCTION BOX DETAIL.....	40
14	CABLE DATA SHEET .....	40
15	(OPTIONAL) PHOTOCCELL DETAIL .....	40
16	(OPTIONAL) MODEM DETAIL .....	40



## 1 GENERAL INFORMATION

The STAR controller and monitoring unit is for lighting structures in accordance with the FAA Advisory Circular AC 707460-1L, CAR 621 and ICAO Annex 14. The Star controller is used with TWR's variety of medium and low intensity obstruction lights.

The STAR lighting system uses digital data communication technology that allows all the lights on the system to be connected via a single TWR Lighting, Inc. LCABLE-1 cable, which combines power and control wires for ease of lighting system installation.

The STAR controller includes a user-friendly interface screen to allow full access and diagnostics at site. There is also ethernet or optional wireless modem for remote monitoring features.

Controller power requirement is 120-240VAC Single phase 50/60Hz and is housed in a metal NEMA 4 enclosure.

Optional STAR controller 24-48VDC model is available.

Each medium intensity obstruction light has a unique identity which allows the STAR controller to control light operation, monitor condition and indicate real time status of the system, including all failures specified by FAA, CAR and ICAO that need to be advised to proper authorities.

### 1.1 Monitoring: Customer Failure Alarm - Dry contact closure (Form C)

#### 1.1.1 Power fail

Monitors incoming and power supply voltage and will therefore indicate if the AC or DC power has failed through an individual relay prewired to normally closed and common. Normally open contact is available.

#### 1.1.2 Beacon White fail

Monitors beacon L865 white LED operation and will therefore indicate if white light has failed through an individual relay prewired to normally closed and common. Normally open contact is available.

#### 1.1.3 Beacon Red fail

Monitors beacon L864 red LED operation and will therefore indicate if red light has failed through an individual relay prewired to normally closed and common. Normally open contact is available.

#### 1.1.4 Mode State Status

Monitors operation status of photocell indicating day or night mode through an individual relay prewired to normally closed and common. Normally open contact is available.

#### 1.1.5 Photocell fail

Monitors Photocell day/night function and will therefore indicate if photocell has failed through an individual relay prewired to normally closed and common. Normally open contact is available.

#### 1.1.6 Sidelight fail

Monitors sidelights L810 red LED operation and will therefore indicate if light has failed through an individual relay prewired to normally closed and common. Normally open contact is available.



### 1.1.7 Communications fail

Monitors communications between STAR controller and lights and will therefore indicate if communications have failed through an individual relay prewired to normally closed and common. Normally open contact is available.

## 1.2 User Interface functions

### 1.2.1 Ethernet/WIFI

Optional for Aircraft Detecting Lighting System (ADLS).

### 1.2.2 Photocell override

TWR's beacon has built-in photocell, but for applications requiring ground level photocell operation there is an optional photocell kit user can install to override beacon Day and Night mode function. Contact TWR service personnel for instructions 713-973-6905 x 4.

## 2 INSTALLATION

Before installing the STAR controller, lights and cable read this manual completely. Check equipment for damage if damage is evident report to TWR technical server before proceeding.

### Suggested tools:

1. Key or Flathead screwdriver to open cabinet
2. #1 flat head screwdriver (small for spring terminal blocks)
3. Flat head #3 Ground lugs
4. Philips #2 for fuse blocks
5. Crescent wrench
6. Electrical Meter

**Note:** System warranty is to be declared null and void if this lighting system is not installed according to instructions and diagrams within this manual.

## 2.1 STAR CONTROLLER (Part # LC-STAR)

### 2.1.1 Controller mounting

The STAR controller enclosure is typically installed at the base of a structure or in an equipment building. It will be necessary to make available a bracket and/or hardware for mounting on structure or equipment building. Refer to mounting dimension on the LC-100 Chassis layout drawing toward the back of this manual.

### 2.1.2 Controller electrical

This controller and lighting system operates on 120/240 VAC 50/60Hz power. Refer to your specific lighting kit drawing at back of manual for operating load to determine breaker size. Optional 24-48 VDC controllers are available. Electrical power input is routed through the base of enclosure by a 3/4" NPT hub. Installation should be in accordance with local methods and National Electrical Codes (NEC).

### 2.1.3 Controller cable for light operation

The standard lighting system uses a single cable to power and control lights. Locate the appropriate 3/4" NPT hub at base of controller enclosure for cable connector install and termination. Use of wire and conduit is optional.



#### 2.1.4 Controller sidelight sensor

Sidelight current sensor is default set at factory to monitor 3x sidelights (L810s) and will therefore indicate if one sidelight has failed through an individual relay prewired to normally closed. Note with so many variables it may be necessary to adjust setting on module to function properly. (Refer to sensor drawing toward the back of this manual.)

#### 2.1.5 Controller alarm monitoring connections

Customer contact point for monitoring beacon and markers/sidelights are provided on terminal block and will therefore indicate if light has failed through a relay prewired to normally closed. Normally open is available.

#### 2.1.6 Controller external photocell (optional)

Monitors Photocell day/night function and will therefore indicate if photocell has failed through an individual relay prewired to normally closed and common. Also, normally open contact is available.

#### 2.1.7 Controller wireless monitoring modem (optional)

Monitors lighting system status through wireless transmission to network operation center or personal device. Contact TWR for more details.

## 2.2 BEACON LIGHT (Part # LONESTAR)



Figure 1: LONESTAR BEACON

#### 2.2.1 Beacon mounting

The Beacon has four mounting feet arranged every 90 degrees on a 13-1/4" bolt hole circle. It will be necessary to have bracket and/or hardware for mounting on structure. Refer to mounting dimension on the Beacon drawing toward the back of this manual.

#### 2.2.2 Beacon electrical

The standard beacon operates on 120/240 VAC 50/60Hz power. Optional 24-48 VDC beacons are available. Refer to the beacon drawing toward the back of this manual.

## 2.3 SIDELIGHT (Part # OL1xxxx)

#### 2.3.1 Sidelight mounting

Sidelight is provided with 3/4" NPT female for mounting. Refer to on the drawing toward the back of this manual.





## 2.4 CABLE (Part # LCABLE-1)

### 2.4.1 Cable specifications

TWR uses a single composite PVC jacketed cable using 3x 12awg (Black, White, and Red) for power, 1x 14awg (Green) for ground and 2x 22awg (Blue, Yellow and Orange, Gray) for communications. All shield wires must be twisted together and terminated to ground. Conduit and wire solutions are available.

### 2.4.2 Cable mounting

Refer to lighting kit layout drawing toward the back of this manual.

### 2.4.3 Cable connection

LCABLE-1 cable uses a cord connector/cable gland over PVC jacket of cable for watertight entry. Refer to drawings toward the back of this manual.

## 3 Operation

Before powering up and operating lighting system you must perform commissioning. TWR technical service is available 24/7 and can assist you with measurements.

### 3.1 LIGHTING SYSTEM COMMISSIONING

#### 3.1.1 COMMISSIONING FORM



**MEDIUM INTENSITY LED  
MODEL LC-STAR**

**Obstacle light system commissioning sheet**

<b>INSTALL DATE:</b>	
<b>SITE ADDRESS:</b>	
<b>COMMISSIONING DATE:</b>	
<b>INSTALLED BY:</b>	
<b>COMMISSIONED BY:</b>	
<b>TWR LIGHTING, INC. ORDER REFERENCE NUMBER:</b>	

<b>SYSTEM INFORMATION</b>	<b>LOCATION ON STRUCTURE</b>
SERIAL # LC-STAR CONTROLLER	
SERIAL # BEACON 1	
SERIAL # BEACON 2	
SERIAL # BEACON 3	
SERIAL # BEACON 4	
SERIAL # BEACON 5	
SERIAL # BEACON 6	
SERIAL # BEACON 7	
SERIAL # BEACON 8	
SERIAL # BEACON 9	
SERIAL # BEACON 10	
SERIAL # BEACON 11	
SERIAL # BEACON 12	

**MEDIUM INTENSITY LED  
MODEL LC-STAR**

**Visual Inspection**

○ Check the lights to ensure that they have not been damaged during installation.
○ Check that all installation terminal connection points are tight and that the wires are connected according to the applicable interconnection diagrams. <b>(TAKE PHOTOS OF WIRING)</b>
○ Check that electrical connections are properly made (no stray wires and properly connected cable glands, etc...) "Outer shield and inner shield cut flush with cable PVC jacket" <b>(TAKE PHOTOS)</b>
○ Check that lights are installed horizontally – use the level indicator on the beacon
○ Check all mechanical installation points (nuts and bolts tight, cables properly secured, etc...)
○ Check that all grounding is properly secure.
○ Check that all System Terminators (Resistors) are installed at the correct points in accordance with the diagrams. <b>(TAKE PHOTOS)</b>



### 3.1.2 IMPEDANCE CHECK

Impedance measurements confirm there are not shorts within wiring indicating all connections are correct. Within the LC-Star controller after completing installation of all components with the system deenergized place your electrical meter setting on Ohms checking the following locations.

<b>*MEASUREMENTS (with a multimeter)</b>		
<b>PASS</b>	<b>FAIL</b>	<b>IMPEDANCE MEASUREMENTS (WITH INPUT POWER OFF)</b>
<input type="radio"/>	<input type="radio"/>	BLUE TO YELLOW = 72.5 OHMS
<input type="radio"/>	<input type="radio"/>	BLUE TO GREY/ORANGE = 560K OHMS
<input type="radio"/>	<input type="radio"/>	YELLOW TO GREY/ORANGE = 560K OHMS
<b>WIRES DISCONNECTED ONLY AT LC-STAR CONTROLLER</b>		
<input type="radio"/>	<input type="radio"/>	BLUE TO YELLOW = 168 OHMS
<input type="radio"/>	<input type="radio"/>	BLUE TO GREY/ORANGE = 506K OHMS
<input type="radio"/>	<input type="radio"/>	YELLOW TO GREY/ORANGE = 506K OHMS

\*MEASUREMENTS MAY VARY WITHIN A FEW PERCENT

#### START-UP

<input type="radio"/>	Connect the power supply to the system.
<input type="radio"/>	1. Check that incoming power supply has the correct voltage and proper protection level. Single phase 120VAC? ( ) 240VAC-“Remove MOV1 before connecting power” ( ) 2. Check voltage at top junction box L-N ( ) L-Ground ( )
<input type="radio"/>	Turn on the power supply and allow the system to initialize. (approx. 1 minute)

Refer to the manual to rectify any system faults – Contact TWR Lighting, Inc. for support: 713.973.6905

## 3.2 STAR CONTROLLER (Part # LC-STAR)




Figure 2: screen and controls


### 3.2.1 Screen and Controls

The Star controller has a screen menu with Up, Down Right and Left cursor blue position push buttons and a red Select/Enter push button. Any menu item with a – to the left of the option will indicate the menu item is Read Only or a Status item and does not have any actions if you press the select button. Items marked with an asterisk \* next to them can be selected / changed or indicate that the item is a sub-menu. Exiting a sub-menu is usually done by pressing the Left / Back button or by scrolling down to a “<Cancel” or “<Back” menu item.


There are a few types of editable fields: Choose, Toggle and Numeric. Choose to present a list of items and you select the item from the list by using the **Up / Down** buttons and Select to choose or press the **Back** button to exit without selecting. Toggle will cycle through different items in place using the **Up/Down** buttons and Select to choose. Fields with editable numeric values will change the character to the left of the value being edited to either a colon “:” or “>” to indicate the **Up/Down** buttons can be used to increment or decrement the value. Typically, the “:” indicates a small change and a “>” indicates a large change but can be reversed depending on what makes sense for the number being edited (a large number vs small). Pressing **Select** to cycle between the increment size or to finalize the change. So, to edit you would press Select once and the edit indicator changes to a “:”. Press Select again and it changes to “>”. Finally pressing Select a third time end the edit.




Numeric Edit Field before editing:




Numeric Edit Field after pressing Select to edit (showing the “:”): The value will change by +/-10 when Up/Down is pressed:



Numeric Edit Field after pressing Select to edit (showing the “>”). The value will change by +/-1 when Up/Down is pressed:




## Menu System Overview



(continues to second diagram)

(continued from diagram 1)




### 3.2.1.1 Main Menu

Depress red select/enter push button to awake the display.

#### 3.2.1.1.1 System (status)


Overall status of the lighting system. Will indicate "OK" when there are no alarms or failures or "ALARMS" when there is a system or lighting issue/alarm.



#### 3.2.1.1.2 Mode (status)

Indicates the current operating mode of the lighting system. The possible modes include:

- **Auto DAY** (photocell day mode)
- **Auto NIGHT** (photocell night mode)
- **Man DAY** (toggle switch photocell override day mode)
- **Man NIGHT** (toggle switch photocell override night mode)
- **Man AUTO** (toggle switch photocell auto mode, will change to Auto Night or Auto Day)
- **White BACKUP** (the night fail backup mode or low intensity white)
- **PCEL FAIL** (photocell has failed and system in white backup)
- **Force OFF** (lights forced off through the menu Mode Override)
- **Force DAY** (lights forced to day mode through the menu Mode Override)
- **Force NIGHT** (lights forced to night mode through the menu Mode Override)



#### 3.2.1.1.3 System Status (submenu)

Pressing Select will display the Status submenu. The status screen will show the various lighting and system status overview and contains the submenus for showing the detailed beacon alarms (see *Beacon Alarms menu*) causes and beacon information (see *Beacon Info menu*).

#### 3.2.1.1.4 Maintenance (submenu)

Depress red select/enter push button to see what how many beacons are connected and type of beacon.

#### 3.2.1.1.5 System Configuration (submenu)

Depress red select/enter push button to see what how many beacons are connected and type of beacon.

#### 3.2.1.1.6 Exit

This menu item, since at the main menu, will cause the LCD to turn off. The display will come on every few minutes then turn back off. Pressing Select while the screen is off will display the last menu it was on.



### 3.2.1.2 System Status Menu

Depress The status screen will show the various lighting and system status overview and contains the submenus for showing the detailed beacon alarms (see *Beacon Alarms menu*) causes and beacon information (see *Beacon Info menu*).

(*System Status Menu*)

```
--Beacon Count: 1
Day: OK
Night: OK
Markers: FAILURE
Comms: OK
Config: OK
Photocell: OK
Mode: Auto Day
PCEL Lvl: 12 Lx
PCEL Tiner: 1134min
GPS Status->
Beacon Alarms->
Beacon Info->
Firmware: 20051316
Board S/N: 4087
<Back
```

#### 3.2.1.2.1 Beacon Count (status)

Shows the number of configured beacons on the system.

#### 3.2.1.2.2 Day (status)

Will indicate “OK” when the day beacons are operating normally or “FAILURE” when an abnormal condition is detected. A detailed reason for the alarm can be found in the Beacon Alarm submenu.

#### 3.2.1.2.3 Night (status)

Will indicate “OK” when the night beacons are operating normally or “FAILURE” when an abnormal condition is detected. A detailed reason for the alarm can be found in the Beacon Alarm submenu.

#### 3.2.1.2.4 Marker/Sidelight (status)

Will indicate “OK” when the side markers are operating normally or “FAILURE” when an undercurrent or flasher failure has been detected (if the Marker option is not disabled in the system settings).

#### 3.2.1.2.5 Comms (status)

Will indicate “OK” when all the beacons are communicating or “FAILURE” when any of the configured beacons have stopped communicating.



### 3.2.1.2.6 Config (status)

Will indicate “**FAILURE**” if the configuration has not been setup or the board has detected a problem with the configuration. This error must be cleared by pressing the Select button, then selecting “**OK**” and pressing Select.

### 3.2.1.2.7 Photocell (status)

Will indicate “**OK**” when the photocell (in the beacons or on the ground depending on the configuration) is changing states within the programmed max time (see Photocell Time under System Configuration menu). If a “**FAILURE**” is shown that would indicate the photocell is not changing modes. A photocell failure will force the system into day mode. If the photocell is set to use the Beacon option, then at least 50% of the photocells must remain operational before a failure will be considered.

### 3.2.1.2.8 Mode (status)

Indicates the current operating mode of the lighting system. The possible modes include:

- **Auto DAY** (photocell day mode)
- **Auto NIGHT** (photocell night mode)
- **Man DAY** (toggle switch photocell override day mode)
- **Man NIGHT** (toggle switch photocell override night mode)
- **Man AUTO** (toggle switch photocell auto mode, will change to Auto Night or Auto Day)
- **White BACKUP** (the night fail backup mode or low intensity white)
- **PCEL FAIL** (photocell has failed and system in white backup)
- **Force OFF** (lights forced off through the menu Mode Override)
- **Force DAY** (lights forced to day mode through the menu Mode Override)
- **Force NIGHT** (lights forced to night mode through the menu Mode Override)

### 3.2.1.2.9 PCEL Level (status)

Displays the light level in Lux if the photocell is configured to use the Beacon photocell.

Example: **PCEL Lvl: 13 Lx**

### 3.2.1.2.10 PCEL Timer (status)


Displays the amount of time remaining in minutes before the photocell is considered failed. The photocell timer setting can be found under the System Configuration menu. 60 = 1hr, 1440 = 19hr

Example: **PCEL Timer: 925min** (in 925 minutes or about 15 hours, if the photocell does not change modes there will be a PCEL Fail alarm).

### 3.2.1.2.11 GPS Status (submenu)

Displays the optional GPS Status submenu showing the GPS signal status, GPS Seconds and Satellite Count.

*(GPS Status Menu)*



- **GPS Sync** – Displays OK if the optional GPS Module is receiving the time and 1PPS pulses or FAILED if either the time or 1PPS is not being received.
- **GPS Seconds** – Displays the current seconds portion of the time received from the GPS



- **Satellite Count** – Shows the number of satellites the GPS receiver is picking up.
- **Loc AMSL** - Displays the estimated height AMSL calculated from the GPS (for reference only)

#### 3.2.1.2.12 Beacon Alarms (submenu)

Displays each beacon and the current alarm status for the currently showing beacon. On a system with more than one beacon the Left / Right buttons will switch between them and shows the beacon address and serial number at the top. The Up / Down buttons will scroll through the list of alarms. Press the Left button once back to beacon 1 to exit the menu. The following are the possible alarm reasons and descriptions:

- **Flshr O/LEDLossThres** – This alarm is set when any LED driver experiences LED voltage loss that exceeds 25% from its Learned value.
- **Flshr O/Photocell** – Indicates if the flasher has been turned off by the photocell
- **Flshr O/CapChgBd** – Indicates if the flasher has been turned off due to a fault with the Capacitor Charge Board
- **Flshr O/Temperature** – Indicates if the flasher has been turned off due to a temperature fault
- **Flshr O/CntDn Timer** – Indicates if the flasher has been turned off due to a count-down timer
- **Flshr O/Forced Off** – Indicates if the flasher has been forced off with an external command
- **Ext Alarm Received** – Indicates an External Alarm has been received from another beacon
- **Err IR LED Open** – Indicates a fault with the IR LEDs caused by an open circuit
- **Err RED LED Open** – Indicates a fault with the RED LEDs caused by an open circuit
- **Err WHT1 LED Open** – Indicates a fault with the White1 strand LEDs caused by an open circuit
- **Err WHT2 LED Open** – Indicates a fault with the White2 strand LEDs caused by an open circuit
- **Err IR LED StkON** – Indicates a fault caused by the IR LEDs being stuck on
- **Err RED LED StkON** – Indicates a fault caused by the RED LEDs being stuck on
- **Err WHT1 LED StkON** – Indicates a fault caused by the White1 strand LEDs being stuck on
- **Err WHT2 LED StkON** – Indicates a fault caused by the White2 strand LEDs being stuck on
- **Err IR Volt Low** – Indicates a low voltage fault with the IR LEDs
- **Err RED Volt Low** – Indicates a low voltage fault with the RED LEDs
- **Err WHT1 Volt Low** – Indicates a low voltage fault with the White1 strand LEDs
- **Err WHT2 Volt Low** – Indicates a low voltage fault with the White2 strand LEDs
- **Err IR Loss Thres** – Indicates a fault caused by an IR LED voltage loss of 25% from its Learned value
- **Err RED Loss Thres** – Indicates a fault caused by a RED LED voltage loss of 25% from its Learned value
- **Err WHT1 Loss Thres** – Indicates a fault caused by a White1 strand LED voltage loss of 25% from its Learned value
- **Err WHT2 Loss Thres** – Indicates a fault caused by a White2 strand LED voltage loss of 25% from its Learned value

#### 3.2.1.2.13 Beacon Info (submenu)

Displays the current status of each beacon. On a system with more than one beacon the Left / Right buttons will switch between them and shows the beacon address and serial number at the top. The Up / Down buttons will scroll through the information. Press the Left button



once back to beacon 1 to exit the menu. The following are the beacon information fields and descriptions of the values:

Field	Example	Description
<b>Boot Ver</b>	200420	The version of the boot firmware loaded on the beacon
<b>App Ver</b>	200406	The version of the application firmware loaded on the beacon
<b>Beacon Type</b>	L865/864_2 40/30fpm	The beacon's configured FAA Classification and Flash rate
<b>PCEL Raw</b>	3091	The current photocell ADC reading (raw value)
<b>PCel <u>Lux</u></b>	15	The current beacon/local photocell Lux value (does not pertain to external photocell if used)
<b>PCel Mode</b>	LOCAL	Indicates the current photo control mode (Local, External or Switch)
<b>Temperature</b>	26	Indicates the Temperature of the LED Assembly in degrees C
<b>CapBd V.In</b>	25.6	Indicates the DC voltage going into the Capacitor Charge Board
<b>CapBd V.PreF</b>	28.0	Indicates the DC voltage out of the Capacitor Charge Board prior to the LEDs firing
<b>CapBd V.PostF</b>	27.9	Indicates the DC voltage out of the Capacitor Charge Board after the LEDs have fired
<b>CapBd I.In</b>	9.1	Indicates the current in mA going into the Capacitor Charge Board
<b>CapBd I.PreF</b>	6.9	Indicates the current in mA out of the Capacitor Charge Board prior to flashing the LEDs
<b>CapBd I.PostF</b>	68.3	Indicates the current in mA out of the Capacitor Charge Board after the LEDs have fired
<b>IR L.PWR</b>	4.6	Indicates the IR LED Power in Watts
<b>RED L.PWR</b>	1.9	Indicates the RED LED Power in Watts
<b>WHT1 L.PWR</b>	7.2	Indicates the WHITE1 strand LED Power in Watts
<b>WHT2 L.PWR</b>	8.7	Indicates the WHITE2 strand LED Power in Watts
<b>IR L.APWR</b>	1.1	Indicates the average IR LED Power in Watts
<b>RED L.APWR</b>	0.4	Indicates the average RED LED Power in Watts
<b>WHT1 L.APWR</b>	1.1	Indicates the average WHITE1 strand LED Power in Watts
<b>WHT2 L.APWR</b>	1.4	Indicates the average WHITE2 strand LED Power in Watts
<b>IR L.Volt</b>	44.4	Indicates the IR LED DC Voltage (V)
<b>RED L.Volt</b>	62.1	Indicates the RED LED DC Voltage (V)

<b>WHT1 L.Volt</b>	128.7	Indicates the WHITE1 strand LED DC Voltage (V)
<b>WHT2 L.Volt</b>	129.0	Indicates the WHITE2 strand LED DC Voltage (V)
<b>IR PWM</b>	0	Indicates the IR PWM rate in %
<b>RED PWM</b>	25	Indicates the RED PWM rate in %
<b>WHT1 PWM</b>	50	Indicates the WHITE1 strand PWM rate in %
<b>WHT2 PWM</b>	50	Indicates the WHITE2 strand PWM rate in %
<b>Flasher Mode</b>	RUNNING	Indicates the operating state of the core flasher module. This may have the value STOPPED, RUNNING, DISABLED, FORCE OFF, or LEARNING.
<b>FlashCode</b>	L864/865 RN 30FPM	Indicates the current FlashCode in use
<b>Active FlashCode</b>	Standard <u>Flashcode</u>	Indicates the active FlashCode set (Standard, Alt1 or Alt2)
<b>Operating Mode</b>	L864/865 RN 30FPM	Indicates the current operating mode (FAA classification, mode, and flash rate)
<b>Active Channels</b>	IR/RED or WHT1/WHT2	Indicates the active LED Drivers / channels in use


#### 3.2.1.2.14 Firmware Version / Board S/N (status)

Shows the lighting controller firmware version and board serial number.

#### 3.2.1.3 Maintenance Menu

The maintenance screen displays a few menu operations that can be used to help diagnose the system or when a beacon is added or removed from the system. Please consult with TWR before using the advanced options.

*(Maintenance Menu)*



### 3.2.1.3.1 Mode Override (option)

Will indicate the current light override mode and can be changed by pressing the Select button and choosing the override mode. If the mode is overridden the PCEL Alarm will be triggered as a reminder that the mode has been overridden. Selecting one of the PERM modes (permanent) will cause the system to operate in the selected mode even after a reset, so use with caution. The possible selections are:

- **Auto/PCL** - Switches back to the normal automatic photocell-based operation.
- **NGT TEMP** - Switches to Night mode temporarily (2 minutes) then switches back to Auto mode.
- **NGT PERM** - Switches to Night mode permanently and will be retained even after a reset.
- **DAY TEMP** - Switches to Day mode temporarily (2 minutes) then switches back to Auto mode.
- **DAY PERM** - Switches to Day mode permanently and will be retained even after a reset.
- **OFF TEMP** - Switches the beacons off temporarily (2 minutes) then switches back to Auto mode.
- **OFF PERM** - Switches the beacons off permanently and will be retained even after a reset.

### 3.2.1.3.2 Start Self-Test (action)

Selecting this action then selecting "Yes" will run through all of the lighting modes checking for failures before switching each mode off then checks for failures after the beacon has been turned off to make sure there are no preexisting failures or alarm and that the beacon is correctly detecting it has been switched off. If the system has the Markers / Sidelight option enabled, they will be tested also by turning off power to the markers while keeping the marker current sensor enabled. The final test status will be displayed after completion and the Up / Down button can be used to scroll through the history.

### 3.2.1.3.3 Poll / Add Beacons (action)

Selecting this action will scan the system for all beacons that are communicating and shows the beacon address (Modbus / BCN#) and Serial Number along with an indication (a "+" at the end of the line) if the beacon is not configured. Use the Up/Down buttons to go through the list. Pressing the Select button on a beacon line will give the option to set the beacon address (*by pressing Select on the Chng BCN Addr option*) and Add it to the system if it is new or Update the beacon Address if it already exists in the configuration. It is recommended that the top beacon be assigned address 1. Valid range is 1-254

*(showing beacon poll results. New beacons will show the "+" at the end)*

```
Results, New=(+)
*BCN1:           1087
  BCN2:           1095+
```

*(showing beacon poll options when selecting a beacon that exists in config)*

```
BCN1:           1087
*Chng BCN Addr# 1
  Update this Beacon
```

### 3.2.1.3.4 Remove Beacon (locked action / contact customer support)

Selecting this action will show the list of configured beacons and give the option to remove a beacon from the system. This can be used to remove a beacon that is being replaced. Use the **Up/Down** buttons to go through the list and pressing the **Select** button on a beacon will prompt to remove it.

(Beacon list)

```
*BCN1: 1087
BCN2: 1095
```

(Remove Prompt)

```
Remove BCN menu
*Remove Beacon?
```

(Remove Confirmation)

```
Remove Beacon?
*Yes
Cancel
```

### 3.2.1.3.5 Modbus / ADLS (submenu)

Selecting this action will show the menu for configuring the optional Ethernet/Modbus TCP/ADLS (radar) module. Send the configuration to the module after configuring the appropriate network settings by selecting the "Send Net Config" menu option. The ethernet module will reboot after receiving the new configuration. The current IP Address will always show at the bottom of the System Status menu.

(Modbus/ADLS Menu)

```
*IP Type: DHCP
IP 192.168.001.002
NM 255.255.255.000
GW 192.168.001.001
Modbus Port 1
ADLS Port 1
Send Net Config
<Back
```



### 3.2.1.3.6 IP/NM/GW (option)


Used to configure the IP Address / Netmask and default Gateway on the optional Ethernet Module (part# LP03-100).

*(IP Address option)*




Press the **Select** button to begin editing. The cursor will change to a **block** indicating the current edit position along with showing a colon: after the field name.

*(IP Address showing edit position select)*



Change the edit position using the **UP** and **DOWN** buttons. Once the **block cursor** is at the position that needs editing, press the **Select** button to switch to digit edit mode. The cursor will change to an **underline** below the position being edited as shown below:

*(IP Address showing edit digit mode)*



Once in the edit digit mode showing the underline cursor, use the UP and DOWN buttons to change the number (up to increase and down to decrease). Press the **Select** button to exit digit edit mode and go back to block cursor position select mode. Continue moving to and editing the IP/NW/GW numbers using the above steps. Press the **Select** button twice without making any changes or the **Left** button at any time to complete the edit process.

### 3.2.1.3.7 Send Net Config (action)

Selecting this action will send the network configuration to the Ethernet module which will then reconfigure and reboot.

### 3.2.1.3.8 Enable BCN Comms (option)

This is automatically done anytime the system starts and should only be used if a beacon has been configured with the TX RS485 option turned off for some reason.

### 3.2.1.3.9 Passthru Modbus (option)

This option is for advanced use only and should not be enabled unless instruction by TWR. **There will be no alarm monitoring while this option is enabled, so use with caution.** This option, when enabled, allows all communications with the beacons to be passed through to the USB Communications port on the controller. Set to Disabled by default.

### 3.2.1.3.10 Reset System (option)

This option will cause the controller board to reset.


### 3.2.1.3.11 Start Bootloader (locked action / contact customer support)

This option is for advanced use only and should not be enabled unless instruction by TWR. Allows new firmware to be installed or updated. Selecting this option will stop all functionality until the board is reset.

### 3.2.1.4 System Configuration Menu (locked menu / contact customer support)

The system configuration screen is where all the system and beacon parameters are configured. Please consult with TWR before changing any settings.


(System Configuration Menu)



#### 3.2.1.4.1 Photocell (option)

The Photocell option is used to tell the controller what type of photocell will be used to detect the light levels used to switch modes. The two options are **Beacon** and **External**. If set to the **Beacon** option, the system will use the light levels (Lux) reported by each beacon to determine when to switch modes. When configured this way, a majority of the beacon photo sensors must agree in order to switch modes. Setting this option to **External** will use a standard 120VAC photocell attached to the light controller to control when the modes are switched between day and night.


(Photocell Option)



#### 3.2.1.4.2 Markers (option)

The Markers option is used to tell the controller what mode the L810 side markers will use. The options are **Disabled** (if no markers are connected), **Steady** (steady burn or on solid / not flashing), and **Flashing** (Set if FAA calls for "Avian" markers). The Flashing mode flashes the markers according to the *Marker Period* and *Marker On Time* configuration under the *System Settings* menu and should match the beacon flash rate.

(Marker Options)



#### 3.2.1.4.3 GPS Sync (option)


**Enables** or **Disables** beacon synchronization using the optional GPS Sync module. Enabling this option requires that the **M2** module is installed on the LP01-100 board and that the GPS antenna is installed. The beacons and (flashing/avian) markers can be configured to flash in sync with other lighting systems using the *Sync Seconds*, *BCN Offset*, and *MRK Offset* settings in the *System Settings* menu. When this option is enabled, the GPS Alarm will activate if no signal is received from the GPS module within the configured *GPS Timeout* setting.



#### 3.2.1.4.4 System Settings (submenu)

Depress red select/enter push button to go into the system settings menu where the fail timers, marker timing and offsets, and GPS sync seconds can be configured.

(System Settings menu)



#### 3.2.1.4.5 PC Fail Hrs. (setting)

This setting configures the number of Hours of not detecting any transition of the photocell before the Photocell (PCEL) Alarm triggers and the PCEL status indicator will light Red. Pressing Select button will display a “:” in front of the hours to indicate edit mode. Use the Up/Down buttons to increase or decrease the value by 1. Pressing Select button again will change the “:” to “>” indicating the Up/Down buttons now will increase or decrease the value by 5. Press Select button again to stop editing. The recommended value is between 19 and 24 hours. Valid range is 0-48hr.

#### 3.2.1.4.6 GPS Timeout (setting)

This setting configures the number of Seconds of not detecting any update from the optional GPS Sync module before the GPS Alarm triggers and the GPS status indicator will light Red. Pressing Select button will display a “:” in front of the seconds to indicate edit mode. Use the Up/Down buttons to increase or decrease the value by 1. Pressing Select button again will change the “:” to “>” indicating the Up/Down buttons now will increase or decrease the value by 10. Press Select button again to stop editing. The recommended value is 60 seconds. Valid range is 0-1200s.

#### 3.2.1.4.7 COM Timeout (setting)

This setting configures the number of Seconds of not detecting any beacon communications over the RS485 connection before the COM Alarm triggers and the COM status indicator will light Red. A beacon communications failure will also trigger a Day and Night alarm just in case the COM alarm is not monitored. The Beacon Status menu will show which beacons are not communicating by showing the beacon as Missing. Pressing Select button will display a “:” in front of the seconds to indicate edit mode. Use the Up/Down buttons to increase or decrease the value by 1. Pressing Select button again will change the “:” to “>” indicating the Up/Down buttons now will increase or decrease the value by 10. Press Select button again to stop editing. The recommended value is 60 seconds. Valid range is 0-600s.



#### 3.2.1.4.8 MRK Period (setting)

The Marker Period configures how long (in milliseconds) the side markers period (on and off time) will be and is only valid if the markers are set to *Flashing*. The period should be set to the same period of the beacon flash rate (2000 for 30FPM, 3000 for 20FPM, 1500 for 40FPM and 1000 for 60FPM). Pressing Select button will display a “:” in front of the value to indicate edit mode. Use the Up/Down buttons to increase or decrease the value by 25ms. Pressing Select button again will change the “:” to “>” indicating the Up/Down buttons now will increase or decrease the value by 1ms. Press Select button again to stop editing. The recommended value is 2000 for avian markers so it will match a beacon set to 30FPM. Valid range is 0-4000ms.

#### 3.2.1.4.9 MRK OnTime (setting)

The Marker On Time configures how long (in milliseconds) the side markers will be turned on and is only valid if the markers are set to *Flashing*. The on time should be set to the same on time of the beacon. Pressing Select button will display a “:” in front of the value to indicate edit mode. Use the Up/Down buttons to increase or decrease the value by 25ms. Pressing Select button again will change the “:” to “>” indicating the Up/Down buttons now will increase or decrease the value by 1ms. Press Select button again to stop editing. The recommended value is 575 for avian markers so it will match a beacon set to 30FPM. Valid range is 0-3000ms.

#### 3.2.1.4.10 MRK Offset and BCN Offset (setting)

The Marker and Beacon Offset configures how long (in milliseconds) before the marker and beacon the side markers will be turned on from the GPS Sync start. Pressing Select button will display a “:” in front of the value to indicate edit mode. Use the Up/Down buttons to increase or decrease the value by 25ms. Pressing Select button again will change the “:” to “>” indicating the Up/Down buttons now will increase or decrease the value by 1ms. Press Select button again to stop editing. The recommended value is 0 but can be adjusted to add a sync delay to match other lighting systems. Valid MRK range is -4000ms to +8000ms and BCN range is -1000ms to +4000ms.

#### 3.2.1.4.11 Sync Seconds (setting)

The Sync Seconds configures which second at which the GPS Sync will be triggered. Pressing Select button will display a “:” in front of the value to indicate edit mode. Use the Up/Down buttons to increase or decrease the value by 1s. Pressing Select button again will change the “:” to “>” indicating the Up/Down buttons now will increase or decrease the value by 10s. Press Select button again to stop editing. The recommended value is 0 but can be adjusted to 1 or 59 to sync on an odd second to match other lighting systems if needed. Valid range is 0-59.


#### 3.2.1.4.12 Save Configuration (action)

Pressing the Select button will save the current configuration.

#### 3.2.1.4.13 System BCN Settings (submenu)

Depress red select/enter push button to go into the system beacon settings menu where default beacons settings (FAA operation type, flash sequence, photocell lux, etc.) can be entered. These are only used if you are editing a beacon and select the option “**Copy from System**”. This will then copy all these settings over to the current beacon that is being edited and is a way to make sure a beacon has the correct settings if it is ever replaced. All the following descriptions will also apply to the **Configure Beacon** menu and therefore will only be described here.

(System BCN Settings menu)



#### 3.2.1.4.14 Send Sync (option)

**Enables** or **Disables** beacon flash synchronization messages between the beacons when communications between the lighting controller (LP01-100) and the beacons is disconnected or has failed. The beacons listen for messages from the controller and if the messages are not received after 10 minutes, the beacons will start sending the sync messages. This option should be Enabled by default.

#### 3.2.1.4.15 Low Loss Thres ALM (option)

**Enables** or **Disables** the Low Voltage Power Loss Threshold Alarm when an LED driver experiences 25% voltage loss from the learned value. When enabled this will also cause the LED driver to turn off (if in Red night mode in a dual setup it will switch to the White backup). This option is should be Enabled by default.

#### 3.2.1.4.16 IR LED Night (option)

**Enables** or **Disables** the use of the IR (infrared) LED Driver at night that help with better visibility for aircraft pilots using night vision goggles (NVGs) or Aviator Night Vision Image Systems (ANVIS). This option is Enabled by default.

#### 3.2.1.4.17 Photo 24Hr Chk (option)

**Enables** or **Disables** the beacon option to check for photocell changes in a 24hr period and will cause a PCEL alarm if a failure is detected. This option is Enabled by default.

### 3.2.1.4.18 Temp Comp (option)

**Enables** or **Disables** the LED Drivers Temperature Compensation. When enabled the voltage of the drivers will be adjusted to account for temperature changes. This option is Enabled by default.

### 3.2.1.4.19 Temp Alarm Fatal (option)

**Enables** or **Disables** the LED Drivers Temperature Alarm if the temperature of the LED assembly is lower or greater than the set thresholds. This option is Disabled by default.

### 3.2.1.4.20 GPS Time (option)

Configures the beacon GPS Sync option to use either the **UTC** seconds or **GPS** seconds when the onboard beacon GPS Sync option (when beacon is in standalone mode, not the same as the optional M2 GPS Sync module) is enabled.

### 3.2.1.4.21 GPS Sync (option)

**Enables** or **Disables** the onboard beacon GPS Sync option (when beacon is in standalone mode, not the same as the optional M2 GPS Sync module). This option is Disabled by default.

### 3.2.1.4.22 DigIn/Out (submenu)

Displays the Beacon Digital Input / Output configuration menu. Digital output (labeled as Alarm Out on each beacon) can be configured to indicate a beacon alarm, day/night mode, or disabled.

*(DigIn/Out menu)*

```

*DigOut1 STEADY_ALA_
DigOut2 DISABLED
DigIn1 DISABLED
DigIn2 DISABLED
DOut1 Inv Enable
DOut2 Inv Disable
DIn#1 Inv Disable
DIn#2 Inv Disable
<Back
```

### 3.2.1.4.23 DigOut1/2 (option)

Configures the Digital Out1 and Out2 Outputs (DigOut1 is used for the local beacon alarm). Can be one of the following options:

- **DISABLED** – Output will not function
- **TOGGLE\_W/FLASHCODE** – Output toggles in sync with beacon flash rate
- **STEADY\_ALARM** – Output state will change upon an alarm condition. The polarity can be configured with the DOut1/2 Inv option.
- **ONE\_HZ\_PULSE\_OUT** – Outputs a 1Hz pulse if no alarm exists.
- **DAY\_NIGHT\_STATUS** – Output state will follow photocell state.
- **PULSE\_OUT** – Outputs a pulse sync at the start of each flash cycle.

### 3.2.1.4.24 DigIn1/2 (option)

Configures the Digital 1/2 Inputs. Can be one of the following options:

- **DISABLED** – Input will not function.
- **DIMMED\_CONTROL** – When active, will use Alternate Intensity.

- **ALTCODE\_DIMMED** – When active, will use alternate flash code ‘Alt1’ and Alternate Intensity.
- **USE\_ALTCODE** – When active, will use alternate flash code ‘Alt1’
- **FORCEOFF\_STD\_SIG** – When active, this will force the lamp off.
- **FORCEOFF\_1HZ\_SIG** – When a 1Hz signal is present, this will force the lamp off

**3.2.1.4.25**      **DOut1/2 Inv (option)**

Inverts the polarity of the Digital Output when enabled (making the output Normally Closed). Default value: Enabled.


**3.2.1.4.26**      **DInp1/2 Inv (option)**

Inverts the polarity of the Digital Input when enabled. Default value: Disabled.

**3.2.1.4.27**      **Beacon (submenu)**

Displays the Beacon configuration menu. Used to set the FAA Beacon Type (operating mode), Flash Sequence (catenary), Day/Night Lux Threshold (photocell transition points), and Ripple Delay (flash delay).

*(Beacon Menu)*



**3.2.1.4.28**      **OP Mode (option)**

Configures the Digital Out1 and Out2 Outputs (DigOut1 is used for the local beacon alarm). Can be one of the following options:

- **L865 40fpm** – White only 40FPM
- **L866 60fpm** – White only 60FPM
- **L864/865\_1 20/40fpm** – Dual Red/White 20FPM Night / 40FPM Day
- **L864/865\_2 30/40fpm** – Dual Red/White 30FPM Night / 40FPM Day
- **L864/865\_3 40/40fpm** – Dual Red/White 40FPM Night / 40FPM Day
- **L864/865\_4 STDY/40** – Dual Red/White Steady Night / 40FPM Day
- **L864/866\_1 60/60fpm** – Dual Red/White 60FPM Night / 60FPM Day
- **L864/866\_2 STDY/60** – Dual Red/White Steady Night / 60FPM Day
- **WHT ONLY** – White (do not use, testing only)
- **RED ONLY** – Red (do not use, testing only)

**3.2.1.4.29**      **Flash SEQ (option)**

Configures the Flash Sequence of this beacon (mainly used on a Catenary setup). Can be one of the following options:



- **NONE** – Delay time will be defined by the **Ripple Delay** field.
- **MID** – Middle beacon. No delay.
- **TOP** – Top beacon. Delay of 1 x (1/13 of flash cycle), from start of Middle beacon.
- **BOT** – Bottom beacon. Delay of 3 x (1/13 of flash cycle), from start of Middle beacon.

#### 3.2.1.4.30 **Ripple Delay (setting)**

Configures the beacon flash delay from sync command in 50ms increments. This delay is only used if the **Flash SEQ** setting is set to **NONE**. For example: to delay the flash of the beacon by 150ms set the Ripple Delay to a value of 3 (3 x 50ms = 150ms).

#### 3.2.1.4.31 **Modbus Address (setting)**

Configures the beacon's Modbus address used in communications over the RS485 network. This address must be unique between the beacons and recommend setting the top beacon to address 1 then the next level down to address 2 and so on. This address is also used to identify each beacon on the LCD menu. BCN1 would be using Modbus Address 1, BCN2 address 2, etc.

#### 3.2.1.4.32 **Copy Saved Config (option)**

This option is only available in the **Configure Beacon** menu. After being prompted if you wish to proceed, this option will load all the settings that have been previously saved when this beacon was previously edited, allowing you to edit those settings and then optionally send them to the beacon. This option can be used to load the saved settings if a beacon has been replaced and you would like to make sure it has the same settings as before.

#### 3.2.1.4.33 **Copy From System (option)**

This option is only available in the **Configure Beacon** menu. After being prompted if you wish to proceed, this option will load all the settings that have been saved to the **System BCN Settings**, allowing you to edit those settings and then optionally send them to the beacon. This option can be used to load the saved settings if a beacon has been replaced and you would like to make sure it has the same settings as before.

#### 3.2.1.4.34 **Load Defaults (option)**

This option will load the default beacon settings programmed into the firmware (L864/865) and allow you to edit them then Save them (to the beacon and memory). You will be prompted if you wish to proceed before the defaults are loaded.

#### 3.2.1.4.35 **Save Settings (option)**


If the System BCN Settings are being edited this option will save them to non-volatile memory. The System BCN Settings are only used when editing a beacon and select the "**Copy from System**" option which will then load the System BCN Settings and use them for the current beacon being edited.

If a beacon is being edited using the Configure Beacon menu, the Save Settings option will first check to see if the beacon Modbus Address has changed. If it detects that the address changed, the system will send a message to the beacon telling it to change to the new address. Once the settings have been saved to non-volatile memory, the settings are sent to the beacon being edited and take effect immediately.

### 3.2.1.4.36 Configure Beacon (submenu)

Depress red select/enter push button to go into the configure beacon menu. This where the beacon settings (FAA operation type, flash sequence, photocell lux, etc.) can be edited. See the field descriptions above under the **System BCN Settings** menu.

*(Configure Beacon menu)*



### 3.2.1.4.37 Save Settings (action)

This action saves all the configuration to non-volatile memory where it is loaded on boot. This does not write the configuration to the beacons, that should be done with the Save Settings option under the **Config Beacon** menu after you edit each beacon.

## 3.2.2 PCB LED Indicators

The Star controller LED indicators provide quick visual of lighting system condition

- **STATUS** = Beacon Sync – illuminated amber when the “sync” message is sent to the beacons.
- **GPS PPS** = GPS Sync pulse – illuminated green when the satellite sync pulse is received from the optional GPS Sync Module. This sync pulse is used to synchronize the flashing of beacons on multiple towers.
- **RXD / TXD** = Beacon data – the RXD and TXD indicators will blink when data is either received “RXD” from or transmitted “TXD” to the beacons over the RS485 port.
- **MKR** = Marker/Sidelight - illuminated red a marker/sidelight is currently in the “failure” state and not illuminated the markers are “off” or “ok”
- **COM** = Communications with Light - illuminated red is a “failure” of communications to one or more of the beacons. Not illuminated means beacon communications are “ok”





- **GPS** = Global Positioning System (optional) - illuminated red indicates a “failure” in receiving either the GPS 1PPS or the time packets. Not illuminated is “not active” or “ok”
- **PCEL** = Photocell - illuminated red indicates a “failure” in detecting any change in the photocell state within the programmed time period (defaults to 19 hours) or the Manual Mode switch / override menu option is not in the “Auto” mode. Not illuminated is “ok”
- **3.3V** = Board 3.3V Power - illuminated green “good” when the board voltage regulator is putting out the 3.3V needed to power up. Not illuminated or “off” means the board does not have main power or the 3.3V regulator is not working.
- **PWR** = Board powered and processor running - illuminated green “good” when the processor boots and starts running. Not illuminated would indicate a power or processor / firmware issue.
- **RF** = Red Fail - illuminated red “fail” when a red beacon failure is detected. Not illuminated or “off” means the red beacon is ok.
- **WF** = White Fail - illuminated red “fail” when a white beacon failure is detected. Not illuminated or “off” means the white beacon is ok.
- **NGT** = Night Mode - illuminated amber when the system is in “night” mode. Not illuminated or “off” means the system is in Day mode.

### 3.3 BEACON LIGHT (Part # LONESTAR)

#### 3.3.1 Beacon power

TWR uses a single composite PVC cable (LCABLE-1) to provide power (120-240VAC) and data communication to beacon.

Refer to drawing toward the back of this manual.

## 4 Maintenance

This lighting system is constructed to be maintenance free. It is necessary to install all components and perform all tasks and described in this manual.

Testing of opened device under voltage should be avoided if possible and when required should be carried out only by a skilled person who is aware of the hazards involved.

### 4.1 TROUBLESHOOTING

#### 4.1.1 STAR CONTROLLER (Part # LC-STAR)

##### 4.1.1.1 No Power:

1. Check the 5amp or 10amp fuse/breaker “L” at input power.
2. Check that AC power is present at the top of fuse/breaker “L:” and that AC power is present at the AC-DC power supply and green indicator is lit.
3. Check for 24VDC output from AC-DC power supply over to “Power In” terminal on control board LP01-100 and green power indicator is lit.
4. Check for any damaged or obvious power surges on control board LP01-100.
5. Try resetting or power cycling the LC-Star controller.





#### 4.1.1.2 No Mode Change (Beacon Photocell)

1. Check that the mode override switch on control board LP01-100 is in "Auto".
2. Check the Mode under System Status Menu and see what mode the system is in. Should be set to Auto Day/Auto Night. If it shows Night or White backup, then there is a Red Beacon Alarm or a Photocell Alarm and will need to be switched to the backup mode. If it is a photocell alarm the PCEL alarm LED will be lit (or if in any manual override).
3. If manual override is shown (MAN xxx or FORCED xxx) then check under the Maintenance menu and make sure the Mode OVR is set to Auto/PCL (auto photocell mode).
4. Check that all beacons are communicating and do not have a red alarm that will put the system in the backup mode.

#### 4.1.1.3 No Mode Change (External Photocell)

1. Check that the mode override switch on control board LP01-100 is in "Auto".
2. Check the Mode under System Status Menu and see what mode the system is in. Should be set to Auto Day/Auto Night. If it shows Night or White backup, then there is a Red Beacon Alarm or a Photocell Alarm and will need to be switched to the backup mode. If it is a photocell alarm the PCEL alarm LED will be lit (or if in any manual override).
3. If manual override is shown (MAN xxx or FORCED xxx) then check under the Maintenance menu and make sure the Mode OVR is set to Auto/PCL (auto photocell mode).
4. Check that the photocell input changes between 120VAC (in night mode) and 0VAC in day mode.

#### 4.1.1.4 Marker Alarm:

1. Check that the system is configured for Markers under System Configuration screen (options are Disabled, Steady, and Flashing).
2. Check that the markers are visually on in night mode (you may have to use the mode override if using Flashing markers since a marker failure would cause the system to go into white backup).
3. Check the "S" fuse/breaker
4. Check that the StarSF cable is plugged into the EXP2 connector properly.
5. Check that the current sensor is powered when in night mode.
6. Check that the current sensor settings are correct.
7. Check that you have power going up to the markers when in night mode.

#### 4.1.1.5 System in White Backup at night:

1. Check for Avian (flashing) Marker failure.
2. Check for beacon alarms (Red or IR Driver / LED errors).
3. Check the Mode OVR setting under Maintenance screen.

#### 4.1.1.6 GPS Failure:

1. Check that the GPS Sync option is enabled.
2. Check that the GPS module is installed and seated firmly.
3. Check that the GPS antenna cable is screwed on correctly and the antenna has a clear view of the sky.
4. Check the GPS Status under the System Status menu and verify that it has three or more satellites in view.
5. Power cycle the controller.


#### 4.1.1.7 Beacon Alarms:

1. Check the number of beacons is correctly at the top of the System Status screen.
2. Check that the TXD 485 light is flashing regularly. If it flashes, the RXD 485 should also flash in return indicating that there is comms on the RS485 lines.
3. Check that the configured beacons are showing under the System Status Beacon Info screen. If they are missing then check power to the beacons.
4. Make the resistance readings on the RS485 lines.
5. Check if any beacons respond to the POLL option under the Maintenance screen. If they are present, but with different Modbus ID's may be lost configuration or unconfigured replacement.

#### 4.1.2 BEACON LIGHT (Part # LONESTAR)

##### 4.1.2.1 LED Indicators

1. Lonestar Beacon Indicator Legend:



This legend is located on the main PCB in the base of the LoneStar Beacon. The corresponding LED indicators are located on the LP02-101 PCB.

Call TWR Technical Support 713-973-6905 Ext. #6



## 5 MAJOR COMPONENTS PARTS LIST

No spare parts are expected to be needed during the warranty period neither during the commissioning procedure. In case a site requires maintaining some spare parts at hand, the 'SP' marked parts can be bought in advance.

The warranty statement as written in this manual is applicable during the installation and commissioning procedure and daily operation.

QTY.	DESCRIPTION	PART NUMBER	SP
2	1 AMP FUSE	KTK-1	Y
2	3 AMP FUSE	KTK-3	Y
2	5 AMP FUSE	KTK-5	Y
2	10 AMP FUSE	FNQ-10	Y
1	LED SIDELIGHT ALARM SENSOR	RM22JA31MRSP01	Y
1	SURGE PROTECTOR	SPM120	Y
1	STAR MAIN PCB	LP01-100	N
1	POWER SUPPLY	MDR-20-24	N
1	STAR OL SYNCHRONIZED FLASHER	STARSF	N
4	END STOP	8WA1808	N
3	FUSE HOLDER	USM-1	N
13	PHOENIX "ST4" SERIES TERMINALS	CX4XXX	N
1	WIRELESS MODEM RV50	MODEM RV50-LTE (OPTIONAL)	N
1	EXTERNAL PHOTOCCELL	6390-FAA (OPTIONAL)	N
1	TERMINAL BLOCK ASSEMBLY	G1002470	N
1	CAPACITOR CHARGER PCB	LP04-101	N
1	PC CONTROL & MONITORING PCB	LP02-101	N
1	MAIN PCB	LP01-101	N
1	RED-IR LED DRIVER PCB	LP06-101	N
2	WHITE LED DRIVER PCBs	LP05-101	N
1	560,000UF CAPACITOR	STB99016	N
1	POWER SUPPLY PCB	LP01-103	N
1	LED LIGHT ENGINE ASSEMBLY		N
1	GPS PCB	LP01-102 (OPTIONAL)	N



## 6 WARRANTY AND RETURN POLICY

TWR Lighting®, Inc. ("TWR®") warrants its products (other than "LED Product") against defects in design, material (excluding incandescent bulbs) and workmanship for a period ending on the earlier of two (2) years from the date of shipment or one (1) year from the date of installation.

TWR Lighting®, Inc. ("TWR®") warrants its "LED Product" against defects in design, material, and workmanship for a period of five (5) years from the date of shipment. TWR®, at its sole option, will, itself, or through others, repair, replace or refund the purchase price paid for "LED Product" that TWR® verifies as being inoperable due to original design, material, or workmanship. All warranty replacement "LED Product" is warranted only for the remainder of the original warranty of the "LED Product" replaced. Replacement "LED Product" will be equivalent in function, but not necessarily identical, to the replaced "LED Product."

TWR Lighting®, Inc. ("TWR®") warrants its "LED Product" against light degradation for a period of five (5) years from the date of installation. TWR®, at its sole option, will, itself, or through others, repair, replace or refund the purchase price paid for "LED Product" that TWR® verifies as failing to meet 75% of the minimum intensity requirements as defined in the FAA Advisory Circular 150/5345-43G dated

09/26/12. All warranty replacement "LED Product" is warranted only for the remainder of the original warranty of the "LED Product" replaced. Replacement "LED Product" will be equivalent in function, but not necessarily identical, to the replaced "LED Product."

Replacement parts (other than "LED Product") are warranted for 90 days from the date of shipment.

Conditions not covered by this Warranty, or which might void this Warranty are as follows:

- x Improper Installation or Operation
- x Misuse
- x Abuse
- x Unauthorized or Improper Repair or Alteration
- x Accident or Negligence in Use, Storage, Transportation, or Handling
- x Any Acts of God or Nature
- x Non-OEM Parts

**The use of non-OEM parts or modifications to original equipment design will void the manufacturer warranty and could invalidate the assurance of complying with FAA requirements as published in Advisory Circular 150/5345-43.**

Field Service – Repairs are warranted for 90 days from the date of service, except where TWR® has made recommendations that were not adhered to that may cause premature failure on previous repairs. Labor, Travel, and Tower Climb are not covered under warranty. Customer shall be obligated to pay for all incurred charges not related to warranty. All warranty repairs are performed by trained TWR® personnel or dispatched through an extensive network of certified and insured Service Representatives.

Return Terms – You must first contact our Customer Service Department at 713-973-6905 to acquire a Return Merchandise Authorization (RMA) number to return the product(s). Please have the following information available when requesting an RMA number:

- x The contact name and phone number of the tower owner
- x The contact name and phone number of the contractor
- x The site name and number
- x The part number(s)



## Warranty & Return Policy

(continued)

- x The serial number(s) (if any)
- x A description of the problem
- x The billing information
- x The Ship To address

This RMA number must be clearly visible on the outside of the box. If the RMA number is not clearly labeled on the outside of the box, your shipment will be refused. Please ensure the material you are returning is packaged carefully. The warranty is null and void if the product(s) are damaged in the return shipment.

All RMAs must be received by TWR LIGHTING®, INC., 10810 W LITTLE YORK RD. #130, HOUSTON TX 77041-4, within 30 days of issuance.

Upon full compliance with the Return Terms, TWR® will replace, repair and return, or credit product(s) returned by the customer. It is TWR's sole discretion to determine the disposition of the returned item(s).

Replacements – Replacement part(s) will be shipped and billed to the customer for product(s) considered as Warranty, pending return of defective product(s). When available, a certified reconditioned part is shipped as warranty replacement with a Return Merchandise Authorization (RMA) number attached. Upon receipt of returned product(s), inspection, testing, and evaluation will be performed to determine the cause of defect. The customer is then notified of the determination of the testing.

- x Product(s) that is deemed defective and/or unrepairable and covered under warranty - a credit will be issued to the customer's account.
- x Product(s) found to have no defect will be subject to a \$75.00 per hour testing charge (1 hour minimum), which will be invoiced to the customer. At this time, the customer may decide to have the tested part(s) returned and is responsible for the return charges.
- x Product(s) under warranty, which the customer does not wish returned, the customer will be issued a credit against the replacement invoice.

Repair & Return – A Return Merchandise Authorization (RMA) will be issued for all part(s) returned to TWR® for repair. Upon receipt of returned product(s), inspection, testing and evaluation will be performed to determine the cause of defect. The customer is then notified of the determination of the testing. If the returned part(s) is deemed unrepairable, or the returned part(s) is found to have no defect, the customer will be subject to a \$75.00 per hour testing charge (1 hour minimum), which will be invoiced to the customer. Should the returned parts be determined to be repairable, a written estimated cost of repair will be sent to the customer for their written approval prior to any work being performed. To have the tested part(s) repaired and/or returned, the customer must issue a purchase order and is responsible for the return shipping charges.

Return to Stock – Any order that is returned to TWR® for part(s) ordered incorrectly by the customer, or unneeded upon receipt, the customer is required to pay a 20% restocking fee. A credit will be issued once it is determined that the Return Terms are met.

Credits – Credits are issued once it is determined that all the Warranty and Return Terms are met. All credits are processed on Fridays. In the event a Friday falls on a Holiday, the credit will be issued on the following Friday.

Freight – All warranty replacement part(s) will be shipped via ground delivery and paid for by TWR®. Delivery other than ground is the responsibility of the customer.



## Warranty & Return Policy


(continued)

**REMEDIES UNDER THIS WARRANTY ARE LIMITED TO PROVISIONS OF REPLACEMENT PARTS AND REPAIRS AS SPECIFICALLY PROVIDED. IN NO EVENT SHALL TWR® BE LIABLE FOR ANY OTHER LOSSES, DAMAGES, COSTS OR EXPENSES INCURRED BY THE CUSTOMER, INCLUDING, BUT NOT LIMITED TO, LOSS FROM FAILURE OF THE PRODUCT(S) TO OPERATE FOR ANY TIME, AND ALL OTHER DIRECT, INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING ALL PERSONAL INJURY OR PROPERTY DAMAGE DUE TO ALLEGED NEGLIGENCE, OR ANY OTHER LEGAL THEORY WHATSOEVER. THIS WARRANTY IS MADE BY TWR® EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES, WHETHER EXPRESSED OR IMPLIED. WITHOUT LIMITING THE GENERALITY OF THE FORGOING, TWR® MAKES NO WARRANTY OF MERCHANTABILITY OR FITNESS OF THE PRODUCT(S) FOR ANY PARTICULAR PURPOSE. TWR® EXPRESSLY DISCLAIMS ALL OTHER WARRANTIES.**



6.1 RMA FORM


RMA-Form

		<b>RETURN MATERIAL AUTHORIZATION FORM</b>
Please send this form together with the defect product to TWR Lighting, Inc.		
<b>TWR Lighting, Inc. reference RMA #</b>	:	
Date (mm-dd-yyyy)	:	
Number of pages	:	1 of
Customer name	:	
Contact person	:	
Delivery address	:	TWR Lighting, Inc., 10810 W Little York Rd. #130 Houston, Tx 77041
Department	:	Service
Telephone	:	(713) 973-6905
Fax	:	(713) 973-9352
Dear customer,		
Please fill in this form completely and return it to the above fax number without indicating an RMA number. The RMA number will be immediately generated by us. Please complete the following questions. <b>Use one sheet for each item that is returned.</b>		
<b>Customer reference RMA nr.</b>	:	
Site location	:	
Product type	:	
Serial number	:	
Reason for return delivery	:	
Initial TWR Lighting, Inc. PO (order) number	:	
Warranty claimed	:	Yes / No
Replacement product needed in advance?	:	Yes / No
<b>Inspection costs in the amount of \$75.00 will be charged for each product. When a replacement product is ordered, the inspection cost will be calculated in the price.</b>		





- 7 CONTROLLER CHASSIS LAYOUT
- 8 CONTROLLER SCHEMATIC
- 9 SIDELIGHT MODULE DETAILS
- 10 LIGHTING KITS
- 11 LONESTAR BEACON DETAIL
- 12 SIDELIGHT L810 DETAIL
- 13 JUNCTION BOX DETAIL
- 14 CABLE DATA SHEET
- 15 (OPTIONAL) PHOTOCCELL DETAIL
- 16 (OPTIONAL) MODEM DETAIL





ITEM NO.	TWR PART NO.	DESCRIPTION
1	LP01-100	STAR MAIN PCB
2	STARSF	SYNCHRONIZED FLASHER
3	RM22JA31MRSP01	SIDLIGHT CURRENT SENSOR
4	MDR-20-24	POWER SUPPLY 120/240VAC TO 24VDC
5	SMP120	SURGE ARRESTOR 120 VAC
6	USM-1	FUSE SWITCH
7	CX4XXX	4 SERIES TERMINALS
8	CX2.5XXX	2.5 SERIES TERMINALS
9	CA103	TERMINAL END STOP
10	MODEM RV50-LTE	WIRELESS MODEM RV50 (OPTIONAL)
11	6390-FAA	EXTERNAL PHOTOCELL (OPTIONAL)

- NOTES:
- 1) THIS DRAWING IS PROVIDED AS GENERAL REFERENCE. TWR LIGHTING INC. DOCUMENTATION SUPERCEDES THIS DRAWING AND SHOULD BE REVIEWED PRIOR TO INSTALLATION OF THIS SYSTEM.
  - 2) WIRES ARE CONNECTED LETTER TO LETTER. EXAMPLE N1 TO N1, N2 TO N2.
  - 3) INPUT POWER SHOULD BE PER NEC.
  - 4) FOR LIGHTING SYSTEMS USING INPUT VOLTAGE 230VAC REMOVE MOV1




**STAR CONTROLLER (LC-STAR)**  
120/230 VAC 50-60Hz

APPROVED BY		
APPROVED BY		
APPROVED BY		
DRAWN BY	SIZE	SHEET QTY.
J.ZAMORANO	B	1 OF 2
DATE	SCALE	DWG. NO.
03/11/2020	N.T.S.	LC-100

**TWR**  
Enlightened Technology

The use of non-OEM parts or modifications to original equipment design will void the manufacturer warranty and could invalidate the assurance of complying with FAA requirements as published in Advisory Circular 150/5345-43.  
NOTICE: The drawings and photographic images contained herein are the sole property of TWR Lighting, Inc. All information contained herein that is not generally known shall be considered confidential except to the extent the information has been previously established. The drawings and photographic images contained herein may not be reproduced, copied or used as the basis for manufacture or sale or promotion or any other purpose without the expressed written permission of TWR Lighting, Inc.



ITEM NO.	TWR PART NO.	DESCRIPTION
1	LP01-100	STAR MAIN PCB
2	STARSF	SYNCHRONIZED FLASHER
3	RM22JA31MRSP01	SIDELIGHT CURRENT SENSOR
4	MDR-20-24	POWER SUPPLY 120/240VAC TO 24VDC
5	SMP120	SURGE ARRESTOR 120 VAC
6	USM-1	FUSE SWITCH
7	CX4XXX	4 SERIES TERMINALS
8	CX2.5XXX	2.5 SERIES TERMINALS
9	CA103	TERMINAL END STOP
10	MODEM RV50-LTE	WIRELESS MODEM RV50 (OPTIONAL)
11	6390-FAA	EXTERNAL PHOTOCELL (OPTIONAL)

- NOTES:
- 1) THIS DRAWING IS PROVIDED AS GENERAL REFERENCE. TWR LIGHTING INC. DOCUMENTATION SUPERCEDES THIS DRAWING AND SHOULD BE REVIEWED PRIOR TO INSTALLATION OF THIS SYSTEM.
  - 2) WIRES ARE CONNECTED LETTER TO LETTER. EXAMPLE N1 TO N1, N2 TO N2.
  - 3) INPUT POWER SHOULD BE PER NEC.
  - 4) FOR LIGHTING SYSTEMS USING INPUT VOLTAGE 230VAC REMOVE MOV1

DRY CONTACT ALARMS	
CONNECTION POINT	DESCRIPTION
SL-NC	SIDELIGHT FAILURE
PF-NC	POWER FAILURE
RF-NC	RED LED FAILURE
WF-NC	WHITE LED FAILURE
MD-NC	MODE DAY/NIGHT OPERATION
PC-NC	PHOTOCELL FAILURE
COM	ALARM COMMON (JUMPER ALL COM POINTS)
BELOW ALARMS ARE OPTIONAL	
GPS-NC	GPS FAILURE
CM-NC	CUSTOMIZABLE ALARM

ALARM STANDARD IS NORMALLY CLOSE (NC)

**STAR CONTROLLER (LC-STAR)**  
120/230 VAC 50-60Hz

APPROVED BY \_\_\_\_\_

APPROVED BY \_\_\_\_\_


APPROVED BY \_\_\_\_\_

DRAWN BY J.ZAMORANO    SIZE B    SHEET QTY. 2 OF 2


DATE 03/11/2020    SCALE N.T.S.    DWG. NO. LC-100

**TWR**  
Enlightened Technology

The use of non-OEM parts or modifications to original equipment design will void the manufacturer warranty and could invalidate the assurance of complying with FAA requirements as published in Advisory Circular 150/5345-43.  
NOTICE: The drawings and photographic images contained herein are the sole property of TWR Lighting, Inc. All information contained herein that is not generally known shall be considered confidential except to the extent the information has been previously established. The drawings and photographic images contained herein may not be reproduced, copied or used as the basis for manufacture or sale or promotion or any other purpose without the expressed written permission of TWR Lighting, Inc.



LED LIGHT ENGINE ASSEMBLY



CABLE GLAND (P/N S2521)

DUAL LED BEACON (P/N LONESTAR)  
MAJOR COMPONENTS

PROD DEPT	<b>TWR Lighting, Inc.</b> Enlightened Technology®				
SERV DEPT					
ENGINEER					
DRAWN BY	J.ZAMORANO	SHEET SIZE	B	SHEET QTY.	1 OF 1
DATE	6/29/2020	SCALE	N.T.S	DWG. NO.	101187

The use of non-OEM parts or modifications to original equipment design will void the manufacturer warranty and could invalidate the assurance of complying with FAA requirements as published in Advisory Circular 150/5345-43.  
NOTICE: The drawings and photographic images contained herein are the sole property of TWR Lighting, Inc. All information contained herein that is not generally known shall be considered confidential except to the extent the information has been previously established. The drawings and photographic images contained herein may not be reproduced, copied or used as the basis for manufacture or sale or promotion or any other purpose without the expressed written permission of TWR Lighting, Inc.

# AC UNITS CURRENT MEASUREMENT RM22JA31MRSP01

## 120VAC PRODUCT SPECIFIC SETTINGS

QTY.	PART NO.	INPUT	#1	#2	#3	#4	#5	PRD.
1	OL1_LED2	E2	*<1	30	20	30	OFF	TWR
2	OL1_LED2	E2	*<1	50	20	30	OFF	TWR
3	OL1_LED2	E3	*<1	20	20	30	OFF	TWR
4	OL1_LED2	E3	*<1	25	20	30	OFF	TWR
6	OL1_LED2	E3	*<1	35	20	30	OFF	TWR
8	OL1_LED2	E3	*<1	45	15	30	OFF	TWR
10	OL1_LED2	E3	*<1	60	10	30	OFF	TWR
1	LEDBEACON2	E3	*<1	25	20	30	OFF	ORGA
1	LEDBEACON2A	E3	*<1	20	20	30	OFF	ORGA
1	LEDBEACON2(T)	E3	*<1	30	20	30	OFF	ORGA
1	STLDBEACON2	E3	*<1	25	20	30	OFF	ORGA
1	STLDBEACON2A	E3	*<1	20	20	30	OFF	ORGA

\*NO MEMORY

### FUNCTIONS

- 1) Configuration: Selection of operation mode (<1 / >1 / >1<) with or without memory.
- 2) Adjustment of current threshold as % of setting range.
- 3) Hysteresis adjustment from 5% to 50%.
- 4) Time Delay adjustment from 0.1 to 30sec.
- 5) Diagnostic button.
- 6) Yellow indicator light (**See conditions below**)
- 7) Dial Pointer (Green) LED
  - Steady green LED indicates that supply to the RM22 is present
  - Flashing green LED indicates a setting has been changed that requires a power cycle.

### YELLOW LED CONDITIONS

**NOTE: (\*) ASTERISK INDICATES LED CONDITIONS OPERATE OPPOSITE FROM RM22JA31MR MODULE**

- ➔ Steady Burn Fixtures
  - Yellow light \*off : Normal condition (no alarm)
  - Yellow light flashing : Undercurrent condition detected and time delay initiated
  - Yellow light \*on : Alarm condition
- ➔ Flashing Fixtures
  - Yellow light flashing inconsistent : Normal condition (no alarm)
  - Yellow light flashing consistent : Under current condition detected and time delay initiated


**NOTE :** To help troubleshoot or to set the sense current, turn the time delay to 0sec. Adjusting the current setting should only be done if it is known that all the lights are functioning. For Steady Burn adjust the current until the yellow LED comes \*off, and the relay is not dropping in and out. For Flashing Fixtures adjust the current setting until the yellow light starts to flash. This is the normal condition setting. Return the time delay back to 30sec.

- Yellow light \*on : Alarm condition

Due to current draw tolerances slight adjustments to setting #2 may be needed for proper alarming.

CONTROL VOLTAGE INPUT

4-40mA INPUT





\* = OPPOSITE CONDITION ON PREVIOUS MODULES

DWG#101088\_RB

TWR Lighting, Inc.





BILL OF MATERIALS				
ITEM	QTY	UNITS	NAME	DESCRIPTION
1	2	ea	CABLEGRIP3	SINGLE EYE LACE MESH 0.63"-0.74"
2	40	ft	CSO14/3	14AWG / 3-CON. S.O. CORD (FOL OLS)
3	1	ea	JBS-S2	UNIVERSAL MOUNTED JB FOR 2 SIDELIGHTS
4	1	ea	LC-STAR	STAR LIGHTING CONTROLLER
5	0	ft	LCABLE-1	POWER & DATA CABLE (TWR HT. + 65')
6	1	ea	LONESTAR	L864/L865 DUAL LED BEACON
7	2	ea	OL1LED	L-810 LED SIDELIGHT
8	2	ea	OLMOUNTKIT	UNIVERSAL OL MOUNTING KIT
9	0	ea	STCABLTI	STROBE CABLE TIES (TWR HT. + 5 + 20)

~ = ITEMS QUANTITY CALCULATED ACCORDING TO STRUCTURE HEIGHT.

- NOTES:
- THIS DRAWING IS PROVIDED AS A GENERAL REFERENCE. TWR LIGHTING, INC. DOCUMENTATION SUPERSEDES THIS DRAWING & SHOULD BE REVIEWED PRIOR TO INSTALLATION OF THIS SYSTEM.
  - CABLEGRIP3 IS USED TO SUPPORT CABLE BEFORE CORD CONNECTOR AND SERVICE LOOP, THE SINGLE EYE LOOP SHOULD BE ATTACHED TO STRUCTURE SECURELY.
  - IF MOUNT IS NEEDED FOR BEACON USE P/N BMSIDE-1.
  - 4' - 5' SERVICE LOOP TO BE INSTALLED AT EACH LIGHT LEVEL AND BASE OF TOWER. IT IS RECOMMENDED IF YOU HAVE EXCESS CABLE OR, IF LENGTH OF CABLE REQUIRES MORE THAN ONE LOOP THEN EITHER PATTERN IN AN S OR SINE WAVE SHAPE OR CUT EXTRA CABLE AND RE-TERMINATE.
  - BLACK WIRE FROM SIDELIGHTS CONNECTS TO RED TERMINALS
  - LIGHTING CABLES ARE TO BE SUPPORTED OVER TOWER FLANGES TO ENSURE THAT THEY DO NOT RUB OR BREAK OPEN.
  - USE P/N HC6-10 TO SECURE JUNCTION BOX AND SIDELIGHT ASSEMBLY TO STRUCTURE. REFER TO DRAWINGS 101180 & 101138 FOR MORE DETAIL.
  - BARE SHIELD WIRES NEED TO BE TERMINATED IN CONTROLLER AND JUNCTION BOXES.
  - BARE SHIELD WIRES NEED TO BE CUT FLUSH WITH CABLE PVC OUTER JACKET IN EACH BEACON (NOT TERMINATED).


**POWER CONSUMPTION**

- ✓ 12hrs day - 4.0/LC-STAR + 32.0/L865 + 0.0/L810 (36 x 12= 0.432KWh)
- ✓ 12hrs night - 4.0/LC-STAR + 13.0/L864 + 16.0/L810 (33 x 12= 0.396KWh)
- ✓ "24hrs = **0.828 KWh**"

**LE11-2A DUAL LED LIGHTING KIT**  
(TOWERS 200'/61M TO 350'/107M)

APPROVED BY		
APPROVED BY		
APPROVED BY		
DRAWN BY J.ZAMORANO	SIZE B	SHEET QTY. 1 OF 1
DATE 07/02/2020	SCALE N.T.S.	DWG. NO. LK-103

The use of non-OEM parts or modifications to original equipment design will void the manufacturer warranty and could invalidate the assurance of complying with FAA requirements as published in Advisory Circular 150/5345-43.  
NOTICE: The drawings and photographic images contained herein are the sole property of TWR Lighting, Inc. All information contained herein that is not generally known shall be considered confidential except to the extent the information has been previously established. The drawings and photographic images contained herein may not be reproduced, copied or used as the basis for manufacture or sale or promotion or any other purpose without the expressed written permission of TWR Lighting, Inc.



BILL OF MATERIALS				
ITEM	QTY	UNITS	NAME	DESCRIPTION
1	2	ea	CABLEGRIP3	SINGLE EYE LACE MESH 0.63"-0.74"
2	40	ft	CSO14/3	14AWG / 3-CON. S.O. CORD (FOL OLS)
3	1	ea	JBS-S3	UNIVERSAL MOUNTED JB FOR 3 SIDELIGHTS
4	1	ea	LC-STAR	STAR LIGHTING CONTROLLER
5	0	ft	LCABLE-1	POWER & DATA CABLE (TWR HT. + 65')
6	1	ea	LONESTAR	L864/L865 DUAL LED BEACON
7	3	ea	OL1LED	L-810 LED SIDELIGHT
8	3	ea	OLMOUNTKIT	UNIVERSAL OL MOUNTING KIT
9	0	ea	STCABLTI	STROBE CABLE TIES (TWR HT. + 5 + 20)

~ = ITEMS QUANTITY CALCULATED ACCORDING TO STRUCTURE HEIGHT.

- NOTES:
- THIS DRAWING IS PROVIDED AS A GENERAL REFERENCE. TWR LIGHTING, INC. DOCUMENTATION SUPERSEDES THIS DRAWING & SHOULD BE REVIEWED PRIOR TO INSTALLATION OF THIS SYSTEM.
  - CABLEGRIP3 IS USED TO SUPPORT CABLE BEFORE CORD CONNECTOR AND SERVICE LOOP, THE SINGLE EYE LOOP SHOULD BE ATTACHED TO STRUCTURE SECURELY.
  - IF MOUNT IS NEEDED FOR BEACON USE P/N BMSIDE-1.
  - 4' - 5' SERVICE LOOP TO BE INSTALLED AT EACH LIGHT LEVEL AND BASE OF TOWER. IT IS RECOMMENDED IF YOU HAVE EXCESS CABLE OR, IF LENGTH OF CABLE REQUIRES MORE THAN ONE LOOP THEN EITHER PATTERN IN AN S OR SINE WAVE SHAPE OR CUT EXTRA CABLE AND RE-TERMINATE.
  - BLACK WIRE FROM SIDELIGHTS CONNECTS TO RED TERMINALS
  - LIGHTING CABLES ARE TO BE SUPPORTED OVER TOWER FLANGES TO ENSURE THAT THEY DO NOT RUB OR BREAK OPEN.
  - USE P/N HC6-10 TO SECURE SIDELIGHT ASSEMBLY TO STRUCTURE. REFER TO DRAWING 101138 FOR MORE DETAIL.
  - USE P/N HC6-10 TO SECURE JUNCTION BOX TO STRUCTURE. REFER TO DRAWING 101180 FOR MORE DETAIL. ENTRY CONFIGURATION ON JBS-S3 AS FOLLOW; ENTRY (1) TO BEACON, ENTRY (2) TO CONTROLLER, ENTRIES (3-5) TO SIDELIGHTS.
  - BARE SHIELD WIRES NEED TO BE TERMINATED IN CONTROLLER AND JUNCTION BOXES.
  - BARE SHIELD WIRES NEED TO BE CUT FLUSH WITH CABLE PVC OUTER JACKET IN EACH BEACON (NOT TERMINATED).

**POWER CONSUMPTION**


- ✓ 12hrs day - 4.0/LC-STAR + 32.0/L865 + 0.0/L810 (36 x 12= 0.432KWh)
- ✓ 12hrs night - 4.0/LC-STAR + 13.0/L864 + 24.0/L810 (41 x 12= 0.492KWh)
- ✓ "24hrs = 0.924 KWh"

**LE11-3A DUAL LED LIGHTING KIT**  
(TOWERS 200'/61M TO 350'/107M)

APPROVED BY		
APPROVED BY		
APPROVED BY		
DRAWN BY	SIZE	SHEET QTY.
J.ZAMORANO	B	1 OF 1
DATE	SCALE	DWG. NO.
02/27/2020	N.T.S.	LK-101

The use of non-OEM parts or modifications to original equipment design will void the manufacturer warranty and could invalidate the assurance of compliance with FAA requirements as published in Advisory Circular 150/5345-43.  
NOTICE: The drawings and photographic images contained herein are the sole property of TWR Lighting, Inc. All information contained herein that is not generally known shall be considered confidential except to the extent the information has been previously established. The drawings and photographic images contained herein may not be reproduced, copied or used as the basis for manufacture or sale or promotion or any other purpose without the expressed written permission of TWR Lighting, Inc.





BILL OF MATERIALS				
ITEM	QTY	UNITS	NAME	DESCRIPTION
1	2	ea	CABLEGRIP3	SINGLE EYE LACE MESH 0.63"-0.74"
2	40	ft	CSO14/3	14AWG / 3-CON. S.O. CORD (FOL OLS)
3	1	ea	JBS-B2T	TOP LEVEL UNIVERSAL MOUNTED JB 2 BEACONS
4	1	ea	JBS-S3	UNIVERSAL MOUNTED JB FOR 3 SIDELIGHTS
5	1	ea	LC-STAR	STAR LIGHTING CONTROLLER
6	0	ft	LCABLE-1	POWER & DATA CABLE (TWR HT. + 95')
7	2	ea	LONESTAR	L864/L865 DUAL LED BEACON
8	3	ea	OL1LED	L-810 LED SIDELIGHT
9	3	ea	OLMOUNTKIT	UNIVERSAL OL MOUNTING KIT
10	0	ea	STCABLTI	STROBE CABLE TIES (TWR HT. + 5 + 20)

~ = ITEMS QUANTITY CALCULATED ACCORDING TO STRUCTURE HEIGHT.

NOTES:


- THIS DRAWING IS PROVIDED AS A GENERAL REFERENCE. TWR LIGHTING, INC. DOCUMENTATION SUPERSEDES THIS DRAWING & SHOULD BE REVIEWED PRIOR TO INSTALLATION OF THIS SYSTEM.
- CABLEGRIP3 IS USED TO SUPPORT CABLE BEFORE CORD CONNECTOR AND SERVICE LOOP, THE SINGLE EYE LOOP SHOULD BE ATTACHED TO STRUCTURE SECURELY.
- IF MOUNT IS NEEDED FOR BEACON USE P/N BMSIDE-1.
- 4' - 5' SERVICE LOOP TO BE INSTALLED AT EACH LIGHT LEVEL AND BASE OF TOWER. IT IS RECOMMENDED IF YOU HAVE EXCESS CABLE OR, IF LENGTH OF CABLE REQUIRES MORE THAN ONE LOOP THEN EITHER PATTERN IN AN S OR SINE WAVE SHAPE OR CUT EXTRA CABLE AND RE-TERMINATE.
- BLACK WIRE FROM SIDELIGHTS CONNECTS TO RED TERMINALS
- LIGHTING CABLES ARE TO BE SUPPORTED OVER TOWER FLANGES TO ENSURE THAT THEY DO NOT RUB OR BREAK OPEN.
- USE P/N HC6-10 TO SECURE JUNCTION BOX AND SIDELIGHT ASSEMBLY TO STRUCTURE. REFER TO DRAWINGS 101180 & 101138 FOR MORE DETAIL.
- BARE SHIELD WIRES NEED TO BE TERMINATED IN CONTROLLER AND JUNCTION BOXES.
- BARE SHIELD WIRES NEED TO BE CUT FLUSH WITH CABLE PVC OUTER JACKET IN EACH BEACON (NOT TERMINATED).

POWER CONSUMPTION

- ✓ 12hrs day - 4.0/LC-STAR + 64.0/L865 + 0.0/L810 (68 x 12= 0.816KWh)
- ✓ 12hrs night - 4.0/LC-STAR + 26.0/L864 + 24.0/L810 (54 x 12= 0.648KWh)
- ✓ "24hrs = **1.464 KWh**"

<b>LE12-3A DUAL LED LIGHTING KIT</b> (TOWERS 200'/61M TO 350'/107M)			
APPROVED BY		<b>TWR</b> Enlightened Technology	
APPROVED BY			
APPROVED BY			
DRAWN BY	SIZE	SHEET QTY.	
J.ZAMORANO	B	1 OF 1	
DATE	SCALE	DWG. NO.	
07/01/2020	N.T.S.	LK-102	
<small>The use of non-OEM parts or modifications to original equipment design will void the manufacturer warranty and could invalidate the assurance of complying with FAA requirements as published in Advisory Circular 150/5345-43.          NOTICE: The drawings and photographic images contained herein are the sole property of TWR Lighting, Inc. All information contained herein that is not generally known shall be considered confidential except to the extent the information has been previously established. The drawings and photographic images contained herein may not be reproduced, copied or used as the basis for manufacture or sale or promotion or any other purpose without the expressed written permission of TWR Lighting, Inc.</small>			





BILL OF MATERIALS				
ITEM	QTY	UNITS	NAME	DESCRIPTION
1	2	ea	CABLEGRIP3	SINGLE EYE LACE MESH 0.63"-0.74"
2	40	ft	CSO14/3	14AWG / 3-CON. S.O. CORD (FOL OLS)
3	1	ea	JBS-B2T	TOP LEVEL UNIVERSAL MOUNTED JB 2 BEACONS
4	1	ea	JBS-S3	UNIVERSAL MOUNTED JB FOR 3 SIDELIGHTS
5	1	ea	LC-STAR	STAR LIGHTING CONTROLLER
6	0	ft	LCABLE-1	POWER & DATA CABLE (TWR HT. + 95')
7	2	ea	LONESTAR	L864/L865 DUAL LED BEACON
8	3	ea	OL1LED	L-810 LED SIDELIGHT
9	3	ea	OLMOUNTKIT	UNIVERSAL OL MOUNTING KIT
10	0	ea	STCABLTIE	STROBE CABLE TIES (TWR HT. ÷ 5 + 20)

~ = ITEMS QUANTITY CALCULATED ACCORDING TO STRUCTURE HEIGHT.

NOTES:


- THIS DRAWING IS PROVIDED AS A GENERAL REFERENCE. TWR LIGHTING, INC. DOCUMENTATION SUPERSEDES THIS DRAWING & SHOULD BE REVIEWED PRIOR TO INSTALLATION OF THIS SYSTEM.
- CABLEGRIP3 IS USED TO SUPPORT CABLE BEFORE CORD CONNECTOR AND SERVICE LOOP, THE SINGLE EYE LOOP SHOULD BE ATTACHED TO STRUCTURE SECURELY.
- IF MOUNT IS NEEDED FOR BEACON USE P/N BMSIDE-1.
- 4' - 5' SERVICE LOOP TO BE INSTALLED AT EACH LIGHT LEVEL AND BASE OF TOWER. IT IS RECOMMENDED IF YOU HAVE EXCESS CABLE OR, IF LENGTH OF CABLE REQUIRES MORE THAN ONE LOOP THEN EITHER PATTERN IN AN S OR SINE WAVE SHAPE OR CUT EXTRA CABLE AND RE-TERMINATE.
- BLACK WIRE FROM SIDELIGHTS CONNECTS TO RED TERMINALS
- LIGHTING CABLES ARE TO BE SUPPORTED OVER TOWER FLANGES TO ENSURE THAT THEY DO NOT RUB OR BREAK OPEN.
- USE P/N HC6-10 TO SECURE JUNCTION BOX AND SIDELIGHT ASSEMBLY TO STRUCTURE. REFER TO DRAWINGS 101180 & 101138 FOR MORE DETAIL.
- BARE SHIELD WIRES NEED TO BE TERMINATED IN CONTROLLER AND JUNCTION BOXES.
- BARE SHIELD WIRES NEED TO BE CUT FLUSH WITH CABLE PVC OUTER JACKET IN EACH BEACON (NOT TERMINATED).

**POWER CONSUMPTION**

- ✓ 12hrs day - 4.0/LC-STAR + 64.0/L865 + 0.0/L810 (68 x 12= 0.816KWh)
- ✓ 12hrs night - 4.0/LC-STAR + 26.0/L864 + 24.0/L810 (54 x 12= 0.648KWh)
- ✓ "24hrs = **1.464 KWh**"

<b>LE12-3A DUAL LED LIGHTING KIT</b>			
<b>(TOWERS 200'/61M TO 350'/107M)</b>			
APPROVED BY		<b>TWR</b> <i>Enlightened Technology</i>	
APPROVED BY			
APPROVED BY			
DRAWN BY J.ZAMORANO		SIZE B	SHEET QTY. 1 OF 1
DATE 07/01/2020		SCALE N.T.S.	DWG. NO. LK-102
<small>The use of non-OEM parts or modifications to original equipment design will void the manufacturer warranty and could invalidate the assurance of complying with FAA requirements as published in Advisory Circular 150/5345-43.</small>			
<small>NOTICE: The drawings and photographic images contained herein are the sole property of TWR Lighting, Inc. All information contained herein that is not generally known shall be considered confidential except to the extent the information has been previously established. The drawings and photographic images contained herein may not be reproduced, copied or used as the basis for manufacture or sale or promotion or any other purpose without the expressed written permission of TWR Lighting, Inc.</small>			





BILL OF MATERIALS					
ITEM	QTY	UNITS	NAME	DESCRIPTION	
1	2	ea	CABLEGRIP3	SINGLE EYE LACE MESH 0.63"-0.74"	
2	1	ea	JBS-B2	UNIVERSAL MOUNTED JB FOR 2 BEACONS	
3	1	ea	LC-STAR	STAR LIGHTING CONTROLLER	
4	0	ft	LCABLE-1	POWER & DATA CABLE (TWR HT. + 95')	
5	3	ea	LONESTAR	L864/L865 DUAL LED BEACON	
6	0	ea	STCABLTIIE	STROBE CABLE TIES (TWR HT. + 5 + 20)	

~ = ITEMS QUANTITY CALCULATED ACCORDING TO STRUCTURE HEIGHT.

NOTES:


- THIS DRAWING IS PROVIDED AS A GENERAL REFERENCE. TWR LIGHTING, INC. DOCUMENTATION SUPERSEDES THIS DRAWING & SHOULD BE REVIEWED PRIOR TO INSTALLATION OF THIS SYSTEM.
- CABLEGRIP3 IS USED TO SUPPORT CABLE BEFORE CORD CONNECTOR AND SERVICE LOOP, THE SINGLE EYE LOOP SHOULD BE ATTACHED TO STRUCTURE SECURELY.
- IF MOUNT IS NEEDED FOR BEACON USE PART #BMSIDE-1.
- 4' - 5' SERVICE LOOP TO BE INSTALLED AT EACH LIGHT LEVEL AND BASE OF TOWER. IT IS RECOMMENDED IF YOU HAVE EXCESS CABLE OR, IF LENGTH OF CABLE REQUIRES MORE THAN ONE LOOP THEN EITHER PATTERN IN AN S OR SINE WAVE SHAPE OR CUT EXTRA CABLE AND RE-TERMINATE.
- LIGHTING CABLES ARE TO BE SUPPORTED OVER TOWER FLANGES TO ENSURE THAT THEY DO NOT RUB OR BREAK OPEN.
- USE P/N HC6-10 TO SECURE JUNCTION BOX TO STRUCTURE. REFER TO DRAWING 101180 FOR MORE DETAIL. ENTRY CONFIGURATION ON JBS-B2 AS FOLLOW; ENTRY (1) TO TOP BEACON, ENTRY (2) TO CONTROLLER, ENTRIES (3 & 4) TO MID LEVEL BEACONS.
- BARE SHIELD WIRES NEED TO BE TERMINATED IN CONTROLLER AND JUNCTION BOXES.
- BARE SHIELD WIRES NEED TO BE CUT FLUSH WITH CABLE PVC OUTER JACKET IN EACH BEACON (NOT TERMINATED).

POWER CONSUMPTION

- ✓ 12hrs day - 4.0/LC-STAR + 96.0/L865 (100 x 12= 1.20KWh)
- ✓ 12hrs night - 4.0/LC-STAR + 39.0/L864 (43 x 12= 0.516KWh)
- ✓ "24hrs = **1.716 KWh**"

<b>LE23-0A DUAL LED LIGHTING KIT</b>			
(TOWERS 350'/107M TO 700'/213M)			
APPROVED BY		<b>TWR</b> Enlightened Technology	
APPROVED BY			
APPROVED BY			
DRAWN BY	SIZE	SHEET QTY.	
J.ZAMORANO	B	1 OF 2	
DATE	SCALE	DWG. NO.	
06/24/2020	N.T.S.	LK-401	

The use of non-OEM parts or modifications to original equipment design will void the manufacturer warranty and could invalidate the assurance of complying with FAA requirements as published in Advisory Circular 150/5345-43.  
 NOTICE: The drawings and photographic images contained herein are the sole property of TWR Lighting, Inc. All information contained herein that is not generally known shall be considered confidential except to the extent the information has been previously established. The drawings and photographic images contained herein may not be reproduced, copied or used as the basis for manufacture or sale or promotion or any other purpose without the expressed written permission of TWR Lighting, Inc.



BILL OF MATERIALS					
ITEM	QTY	UNITS	NAME	DESCRIPTION	
1	2	ea	CABLEGRIP3	SINGLE EYE LACE MESH 0.63"-0.74"	
2	1	ea	JBS-B2	UNIVERSAL MOUNTED JB FOR 2 BEACONS	
3	1	ea	LC-STAR	STAR LIGHTING CONTROLLER	
4	0	ft	LCABLE-1	POWER & DATA CABLE (TWR HT. + 95')	
5	3	ea	LONESTAR	L864/L865 DUAL LED BEACON	
6	0	ea	STCABLTI	STROBE CABLE TIES (TWR HT. + 5 + 20)	

~ = ITEMS QUANTITY CALCULATED ACCORDING TO STRUCTURE HEIGHT.

- NOTES:
- THIS DRAWING IS PROVIDED AS A GENERAL REFERENCE. TWR LIGHTING, INC. DOCUMENTATION SUPERSEDES THIS DRAWING & SHOULD BE REVIEWED PRIOR TO INSTALLATION OF THIS SYSTEM.
  - CABLEGRIP3 IS USED TO SUPPORT CABLE BEFORE CORD CONNECTOR AND SERVICE LOOP, THE SINGLE EYE LOOP SHOULD BE ATTACHED TO STRUCTURE SECURELY.
  - IF MOUNT IS NEEDED FOR BEACON USE PART #BMSIDE-1.
  - 4' - 5' SERVICE LOOP TO BE INSTALLED AT EACH LIGHT LEVEL AND BASE OF TOWER. IT IS RECOMMENDED IF YOU HAVE EXCESS CABLE OR, IF LENGTH OF CABLE REQUIRES MORE THAN ONE LOOP THEN EITHER PATTERN IN AN S OR SINE WAVE SHAPE OR CUT EXTRA CABLE AND RE-TERMINATE.
  - LIGHTING CABLES ARE TO BE SUPPORTED OVER TOWER FLANGES TO ENSURE THAT THEY DO NOT RUB OR BREAK OPEN.
  - USE P/N HC6-10 TO SECURE JUNCTION BOX TO STRUCTURE. REFER TO DRAWING 101180 FOR MORE DETAIL. ENTRY CONFIGURATION ON JBS-B2 AS FOLLOW; ENTRY (1) TO TOP BEACON, ENTRY (2) TO CONTROLLER, ENTRIES (3 & 4) TO MID LEVEL BEACONS.
  - BARE SHIELD WIRES NEED TO BE TERMINATED IN CONTROLLER AND JUNCTION BOXES.
  - BARE SHIELD WIRES NEED TO BE CUT FLUSH WITH CABLE PVC OUTER JACKET IN EACH BEACON (NOT TERMINATED).



**POWER CONSUMPTION**  
 ✓ 12hrs day - 4.0/LC-STAR + 96.0/L865 (100 x 12= 1.20KWh)  
 ✓ 12hrs night - 4.0/LC-STAR + 39.0/L864 (43 x 12= 0.516KWh)  
 ✓ "24hrs = 1.716 KWh"

**LE23-0A DUAL LED LIGHTING KIT**  
 (TOWERS 350'/107M TO 700'/213M)

APPROVED BY		
APPROVED BY		
APPROVED BY		
DRAWN BY	SIZE	SHEET QTY.
J.ZAMORANO	B	2 OF 2
DATE	SCALE	DWG. NO.
06/24/2020	N.T.S.	LK-401

**TWR**  
Enlightened Technology

The use of non-OEM parts or modifications to original equipment design will void the manufacturer warranty and could invalidate the assurance of complying with FAA requirements as published in Advisory Circular 150/5345-43.  
 NOTICE: The drawings and photographic images contained herein are the sole property of TWR Lighting, Inc. All information contained herein that is not generally known shall be considered confidential except to the extent the information has been previously established. The drawings and photographic images contained herein may not be reproduced, copied or used as the basis for manufacture or sale or promotion or any other purpose without the expressed written permission of TWR Lighting, Inc.



BILL OF MATERIALS				
ITEM	QTY	UNITS	NAME	DESCRIPTION
1	2	ea	CABLEGRIP3	SINGLE EYE LACE MESH 0.63"-0.74"
2	40	ft	CSO14/3	14AWG / 3-CON. S.O. CORD (FOL OLS)
3	1	ea	JBS-S3	UNIVERSAL MOUNTED JB FOR 3 SIDELIGHTS
4	1	ea	LC-STAR	STAR LIGHTING CONTROLLER
5	0	ft	LCABLE-1	POWER & DATA CABLE (TWR HT. + 65')
6	1	ea	LONESTAR	L864 RED LED BEACON
7	3	ea	OL1LED	L-810 LED SIDELIGHT
8	3	ea	OLMOUNTKIT	UNIVERSAL OL MOUNTING KIT
9	0	ea	STCABLTI	STROBE CABLE TIES (TWR HT. + 5 + 20)

~ = ITEMS QUANTITY CALCULATED ACCORDING TO STRUCTURE HEIGHT.

- NOTES:
- THIS DRAWING IS PROVIDED AS A GENERAL REFERENCE. TWR LIGHTING, INC. DOCUMENTATION SUPERSEDES THIS DRAWING & SHOULD BE REVIEWED PRIOR TO INSTALLATION OF THIS SYSTEM.
  - CABLEGRIP3 IS USED TO SUPPORT CABLE BEFORE CORD CONNECTOR AND SERVICE LOOP, THE SINGLE EYE LOOP SHOULD BE ATTACHED TO STRUCTURE SECURELY.
  - IF MOUNT IS NEEDED FOR BEACON USE P/N BMSIDE-1.
  - 4' - 5' SERVICE LOOP TO BE INSTALLED AT EACH LIGHT LEVEL AND BASE OF TOWER. IT IS RECOMMENDED IF YOU HAVE EXCESS CABLE OR, IF LENGTH OF CABLE REQUIRES MORE THAN ONE LOOP THEN EITHER PATTERN IN AN S OR SINE WAVE SHAPE OR CUT EXTRA CABLE AND RE-TERMINATE.
  - BLACK WIRE FROM SIDELIGHTS CONNECTS TO RED TERMINALS
  - LIGHTING CABLES ARE TO BE SUPPORTED OVER TOWER FLANGES TO ENSURE THAT THEY DO NOT RUB OR BREAK OPEN.
  - USE P/N HC6-10 TO SECURE SIDELIGHT ASSEMBLY TO STRUCTURE. REFER TO DRAWING 101138 FOR MORE DETAIL.
  - USE P/N HC6-10 TO SECURE JUNCTION BOX TO STRUCTURE. REFER TO DRAWING 101180 FOR MORE DETAIL. ENTRY CONFIGURATION ON JBS-S3 AS FOLLOW; ENTRY (1) TO BEACON, ENTRY (2) TO CONTROLLER, ENTRIES (3-5) TO SIDELIGHTS.
  - BARE SHIELD WIRES NEED TO BE TERMINATED IN CONTROLLER AND JUNCTION BOXES.
  - BARE SHIELD WIRES NEED TO BE CUT FLUSH WITH CABLE PVC OUTER JACKET IN EACH BEACON (NOT TERMINATED).

**POWER CONSUMPTION**


- ✓ 12hrs day - 4.0/LC-STAR + 0.0/L864 + 0.0/L810 (4 x 12= 0.048KWh)
- ✓ 12hrs night - 4.0/LC-STAR + 13.0/L864 + 24.0/L810 (41 x 12= 0.492KWh)
- ✓ "24hrs = **0.540 KWh**"

**LA11-3A RED LED LIGHTING KIT**  
(TOWERS 150'/46M TO 350'/107M)

APPROVED BY		
APPROVED BY		
APPROVED BY		
DRAWN BY	SIZE	SHEET QTY.
J.ZAMORANO	B	1 OF 1
DATE	SCALE	DWG. NO.
07/27/2020	N.T.S.	NK-102

**TWR**  
Enlightened Technology

The use of non-OEM parts or modifications to original equipment design will void the manufacturer warranty and could invalidate the assurance of complying with FAA requirements as published in Advisory Circular 150/5345-43.  
NOTICE: The drawings and photographic images contained herein are the sole property of TWR Lighting, Inc. All information contained herein that is not generally known shall be considered confidential except to the extent the information has been previously established. The drawings and photographic images contained herein may not be reproduced, copied or used as the basis for manufacture or sale or promotion or any other purpose without the expressed written permission of TWR Lighting, Inc.



BILL OF MATERIALS				
ITEM	QTY	UNITS	NAME	DESCRIPTION
1	2	ea	CABLEGRIP3	SINGLE EYE LACE MESH 0.63"-0.74"
2	1	ea	JBS-B2	UNIVERSAL MOUNTED JB FOR 2 BEACONS
3	1	ea	JBS-B2T	TOP LEVEL UNIVERSAL MOUNTED JB 2 BEACONS
4	1	ea	LC-STAR	STAR LIGHTING CONTROLLER
5	0	ft	LCABLE-1	POWER & DATA CABLE (TWR HT. + 125')
6	4	ea	NIGHTSTAR	L864 RED LED BEACON
7	0	ea	STCABLIE	STROBE CABLE TIES (TWR HT. + 5 + 20)

~ = ITEMS QUANTITY CALCULATED ACCORDING TO STRUCTURE HEIGHT.

NOTES:

- 1) THIS DRAWING IS PROVIDED AS A GENERAL REFERENCE. TWR LIGHTING, INC. DOCUMENTATION SUPERSEDES THIS DRAWING & SHOULD BE REVIEWED PRIOR TO INSTALLATION OF THIS SYSTEM.
- 2) CABLEGRIP3 IS USED TO SUPPORT CABLE BEFORE CORD CONNECTOR AND SERVICE LOOP, THE SINGLE EYE LOOP SHOULD BE ATTACHED TO STRUCTURE SECURELY.
- 3) IF MOUNT IS NEEDED FOR BEACON USE PART #BMSIDE-1.
- 4) 4' - 5' SERVICE LOOP TO BE INSTALLED AT EACH LIGHT LEVEL AND BASE OF TOWER. IT IS RECOMMENDED IF YOU HAVE EXCESS CABLE OR, IF LENGTH OF CABLE REQUIRES MORE THAN ONE LOOP THEN EITHER PATTERN IN AN S OR SINE WAVE SHAPE OR CUT EXTRA CABLE AND RE-TERMINATE.
- 5) LIGHTING CABLES ARE TO BE SUPPORTED OVER TOWER FLANGES TO ENSURE THAT THEY DO NOT RUB OR BREAK OPEN.
- 6) USE P/N HC6-10 TO SECURE JUNCTION BOX TO STRUCTURE. REFER TO DRAWING 101180 FOR MORE DETAIL. ENTRY CONFIGURATION ON JBS-B2 AS FOLLOW; ENTRY (1) TO TOP BEACON, ENTRY (2) TO CONTROLLER, ENTRIES (3 & 4) TO MID LEVEL BEACONS.
- 7) BARE SHIELD WIRES NEED TO BE TERMINATED IN CONTROLLER AND JUNCTION BOXES.
- 8) BARE SHIELD WIRES NEED TO BE CUT FLUSH WITH CABLE PVC OUTER JACKET IN EACH BEACON (NOT TERMINATED).

POWER CONSUMPTION


- ✓ 12hrs day - 4.0/LC-STAR + 0.0/L864 (4 x 12= 0.048KWh)
- ✓ 12hrs night - 4.0/LC-STAR + 52.0/L864 (56 x 12= 0.672KWh)
- ✓ "24hrs = 0.720 KWh"

<b>LA24-0A RED LED LIGHTING KIT</b> (TOWERS 350'/107M TO 700'/213M)		
APPROVED BY		
APPROVED BY		
APPROVED BY		
DRAWN BY J.ZAMORANO	SIZE B	SHEET QTY. 1 OF 2
DATE 07/02/2020	SCALE N.T.S.	DWG. NO. NK-402

The use of non-OEM parts or modifications to original equipment design will void the manufacturer warranty and could invalidate the assurance of complying with FAA requirements as published in Advisory Circular 150/5345-43.  
 NOTICE: The drawings and photographic images contained herein are the sole property of TWR Lighting, Inc. All information contained herein that is not generally known shall be considered confidential except to the extent the information has been previously established. The drawings and photographic images contained herein may not be reproduced, copied or used as the basis for manufacture or sale or promotion or any other purpose without the expressed written permission of TWR Lighting, Inc.







BILL OF MATERIALS				
ITEM	QTY	UNITS	NAME	DESCRIPTION
1	2	ea	CABLEGRIP3	SINGLE EYE LACE MESH 0.63"-0.74"
2	1	ea	JBS-B2	UNIVERSAL MOUNTED JB FOR 2 BEACONS
3	1	ea	JBS-B2T	TOP LEVEL UNIVERSAL MOUNTED JB 2 BEACONS
4	1	ea	LC-STAR	STAR LIGHTING CONTROLLER
5	0	ft	LCABLE-1	POWER & DATA CABLE (TWR HT. + 125')
6	4	ea	NIGHTSTAR	L864 RED LED BEACON
7	0	ea	STCABLTI	STROBE CABLE TIES (TWR HT. + 5 + 20)

? = ITEMS QUANTITY CALCULATED ACCORDING TO STRUCTURE HEIGHT.

NOTES:

- THIS DRAWING IS PROVIDED AS A GENERAL REFERENCE. TWR LIGHTING, INC. DOCUMENTATION SUPERSEDES THIS DRAWING & SHOULD BE REVIEWED PRIOR TO INSTALLATION OF THIS SYSTEM.
- CABLEGRIP3 IS USED TO SUPPORT CABLE BEFORE CORD CONNECTOR AND SERVICE LOOP, THE SINGLE EYE LOOP SHOULD BE ATTACHED TO STRUCTURE SECURELY.
- IF MOUNT IS NEEDED FOR BEACON USE PART #BMSIDE-1.
- 4' - 5' SERVICE LOOP TO BE INSTALLED AT EACH LIGHT LEVEL AND BASE OF TOWER. IT IS RECOMMENDED IF YOU HAVE EXCESS CABLE OR, IF LENGTH OF CABLE REQUIRES MORE THAN ONE LOOP THEN EITHER PATTERN IN AN S OR SINE WAVE SHAPE OR CUT EXTRA CABLE AND RE-TERMINATE.
- LIGHTING CABLES ARE TO BE SUPPORTED OVER TOWER FLANGES TO ENSURE THAT THEY DO NOT RUB OR BREAK OPEN.
- USE P/N HC6-10 TO SECURE JUNCTION BOX TO STRUCTURE. REFER TO DRAWING 101180 FOR MORE DETAIL. ENTRY CONFIGURATION ON JBS-B2 AS FOLLOW; ENTRY (1) TO TOP BEACON, ENTRY (2) TO CONTROLLER, ENTRIES (3 & 4) TO MID LEVEL BEACONS.
- BARE SHIELD WIRES NEED TO BE TERMINATED IN CONTROLLER AND JUNCTION BOXES.
- BARE SHIELD WIRES NEED TO BE CUT FLUSH WITH CABLE PVC OUTER JACKET IN EACH BEACON (NOT TERMINATED).

POWER CONSUMPTION


- ✓ 12hrs day - 4.0/LC-STAR + 0.0/L864 (4 x 12= 0.048KWh)
- ✓ 12hrs night - 4.0/LC-STAR + 52.0/L864 (56 x 12= 0.672KWh)
- ✓ "24hrs = **0.720 KWh**"

LA24-0A RED LED LIGHTING KIT  
(TOWERS 350'/107M TO 700'/213M)


APPROVED BY		
APPROVED BY		
APPROVED BY		
DRAWN BY	SIZE	SHEET QTY.
J.ZAMORANO	B	2 OF 2
DATE	SCALE	DWG. NO.
07/02/2020	N.T.S.	NK-402



The use of non-OEM parts or modifications to original equipment design will void the manufacturer warranty and could invalidate the assurance of complying with FAA requirements as published in Advisory Circular 150/5345-43.  
 NOTICE: The drawings and photographic images contained herein are the sole property of TWR Lighting, Inc. All information contained herein that is not generally known shall be considered confidential except to the extent the information has been previously established. The drawings and photographic images contained herein may not be reproduced, copied or used as the basis for manufacture or sale or promotion or any other purpose without the expressed written permission of TWR Lighting, Inc.



LED LIGHT ENGINE ASSEMBLY



DUAL LED BEACON (P/N LONESTAR) MAJOR COMPONENTS					
PROD DEPT		 Enlightened Technology®			
SERV DEPT					
ENGINEER					
DRAWN BY	J.ZAMORANO	SHEET SIZE	B	SHEET QTY.	1 OF 1
DATE	6/29/2020	SCALE	N.T.S	DWG. NO.	101187
<small>           The use of non-OEM parts or modifications to original equipment design will void the manufacturer warranty and could invalidate the assurance of complying with FAA requirements as published in Advisory Circular 150/5345-43.            NOTICE: The drawings and photographic images contained herein are the sole property of TWR Lighting, Inc. All information contained herein that is not generally known shall be considered confidential except to the extent the information has been previously established. The drawings and photographic images contained herein may not be reproduced, copied or used as the basis for manufacture or sale or promotion or any other purpose without the expressed written permission of TWR Lighting, Inc.         </small>					


4

3




2

1

Parts List			
ITEM	QTY	PART NUMBER	DESCRIPTION
1	1	105RCP	RED CAST SINGLE BOTTOM HUB BODY
2	2	HC255SS	SIDELIGHT LATCH
3	1	A314	3/4" CONDUIT LOCKNUT GALV.
4	2	12V245	OL LENS CLIP
5	2	832X14PH	8-32 X 1/4 PH SS SLOT SCREW
6	2	A1A	STAKON CRIMP
7	.5	7X7SS	1/16 HOL 7X7 S.S. WIRE
8	1	PS90-260/24	POWER SUPPLY
9	1	OLG2	OL1 6 LED GASKET
10	1	106CP	RED CAST LENS HOLDER RING
11	1	LED120-2RK	OL16LED 120-240VAC RETROFIT KIT



### DIMENSIONS



\* GROUND WIRE MUST BE CONNECTED TO PROPERLY PROTECT POWER SUPPLY. FAILURE TO GROUND WILL VOID ALL WARRANTIES.

**WEIGHT: 2.2 lbs (0.998kg)**

OL1CBH34LED2 120VAC FAA-OL16LED (L810 OBSTRUCTION LIGHT)			
PROD DEPT	<b>TWR Lighting, Inc. HARK</b> <i>Enlightened Technology®</i>		
SERV DEPT			
ENGINEER			
DRAWN BY	JBUSTAMANTE	SHEET SIZE	B
DATE	6/14/2007	SCALE	
		DWG. NO.	100749i
		SHEET QTY.	1 OF 1

AUTHOR	DATE	REV	DESCRIPTION
J.ZAMORANO	10/23/2015	C	UPDATED DIMS.


4

3


2

1

**BOTTOM HUB INSTALLATION**



**SIDE HUB INSTALLATION**





**NOTES**

1. PART HC6-10 NEEDS TO BE DOUBLED FOR TOWER LEGS WITH A DIAMETER LARGER THEN 6".
2. USE PART HC6-10 PROVIDED WITH JUNCTION BOX TO SECURE ASSEMBLY TO A VERTICAL PORTION OF STRUCTURE. REFERENCE DRAWING 101180.
3. USE PART STCABLETIE TO SECURE CABLE TO THE STRUCTURE.
4. ITEMS 1.1 TO 1.3 ARE INCLUDED WITH ITEM 1. QUANTITIES REFLECT 3 OLMOUNTKITS.

**PARTS LIST**

ITEM	QTY	PART NUMBER	DESCRIPTION
1	3	OLMOUNTKIT	OL UNIVERSAL MOUNTING KIT
1.1	3	101136	OL MOUNTING BRACKET
1.2	1.2	HC6-10	STAINLESS STEEL MOUNTING STRAP 6" DIA.
1.3	3	S2134	3/4" CABLE GLAND 0.512" - 0.709"
2	3	OL1	3/4" BOTTOM OR SIDE HUB SIDE MARKER
3	40'	CSO14/3	14AWG / 3CON. S.O. CORD
4	1	JBS-S3	UNIVERSAL MOUNTED JB FOR 3 OLs
5	6	STCABLETIE	CABLE TIES (FOR CABLE SUPPORT)



**CABLE MOUNTING KIT FOR (3) SIDELIGHTS**

PROD DEPT	<b>TWR Lighting, Inc. MARK</b> <i>Enlightened Technology®</i>				
SERV DEPT					
ENGINEER					
DRAWN BY	J.ZAMORANO	SHEET SIZE	B	SHEET QTY.	1 OF 1
DATE	3/19/2019	SCALE	N.T.S	DWG. NO.	101138

REV	AUTHOR	DATE	DESCRIPTION
B	J.ZAMORANO	6/1/2020	UPDATED JUNCTION BOX

The use of non-OEM parts or modifications to original equipment design will void the manufacturer warranty and could invalidate the assurance of complying with FAA requirements as published in Advisory Circular 150/5345-43.  
NOTICE: The drawings and photographic images contained herein are the sole property of TWR Lighting, Inc. All information contained herein that is not generally known shall be considered confidential except to the extent the information has been previously established. The drawings and photographic images contained herein may not be reproduced, copied or used as the basis for manufacture or sale or promotion or any other purpose without the expressed written permission of TWR Lighting, Inc.



4

3

2

1

B

B

A



A

IT IS RECOMENDED TO ADD  
A THIRD STRAP TO SECURE  
JUNCTION BOX TO STRUCTURE


STAINLESS STEEL STRAP PN. HC6-10  
PROVIDED WITH JUNCTION BOX

JUNCTION BOX PN. JBX-XXX

4X Ø1/2" HOLES  
FOR WALL MOUNTING



QUARTER TURN LOCKS CAN BE UNLOCKED  
WITH PROVIDED KEY OR FLAT HEAD SCREWDRIVER



### JUNCTION BOX MOUNTING DETAIL

PROD DEPT  
SERV DEPT  
ENGINEER

**TWR Lighting, Inc.**  
Enlightened Technology®

DRAWN BY J.ZAMORANO

SHEET SIZE B SHEET QTY. 1 OF 1

DATE 05/19/2020

SCALE N.T.S

DWG. NO. 101180

The use of non-OEM parts or modifications to original equipment design will void the manufacturer warranty and could invalidate the assurance of complying with FAA requirements as published in Advisory Circular 150/5345-43.  
NOTICE: The drawings and photographic images contained herein are the sole property of TWR Lighting, Inc. All information contained herein that is not generally known shall be considered confidential except to the extent the information has been previously established. The drawings and photographic images contained herein may not be reproduced, copied or used as the basis for manufacture or sale or promotion or any other purpose without the expressed written permission of TWR Lighting, Inc.


4

3

4

2

1



SPECIFICATION  
HILS STROBE CABLE

CONDUCTOR NUMBER	AWG	TINNED COPPER WIRE STRAND	INSULATION VOLTAGE	COLOR
1	12	65/30 STRANDED	300V MIN.	BLACK
2	12	65/30 STRANDED	300V MIN.	RED
3	12	65/30 STRANDED	300V MIN.	WHITE
4	14	41/30 STRANDED	300V MIN.	GREEN
5	22	7/30 STRANDED	300V MIN.	BLUE
6	22	7/30 STRANDED	300V MIN.	YELLOW
7	22	7/30 STRANDED	300V MIN.	ORANGE
8	22	7/30 STRANDED	300V MIN.	GRAY
9	22	7/30 STD BARE	NONE	BARE
10	22	7/30 STD BARE	NONE	BARE
11	14	41/30 STD BARE	NONE	BARE

GENERAL: 3X12AWG, 1X14AWG ISP PVC COMPOSITE CABLE

3 CONDUCTORS (12 AWG):

COLOR CODE: BLACK, WHITE, RED

1 CONDUCTOR (14 AWG):

COLOR CODE: GREEN

2 SHIELDED PAIR: (22 AWG):

COLOR CODE: ORANGE / YELLOW / SHIELD

RATING:

UL-2464

300 VOLTS

80 DEGREE CENTIGRADE

CSA AWM 1/II A/B

LCABLE-1 (LED CABLE)

**TWR Lighting, Inc.**

APP'D	ENGINEER	CHK'D BY
DRAWN BY G.D.S.		SHEET SIZE A
DATE 10/25/2019		SHEET QTY. 1 OF 1
SCALE N.T.S.	DRAWING NO. F01-111SL	

NOTICE: This drawing is the property of TWR Lighting, Inc. All information contained herein that is not generally known shall be confidential except to the extent the information has been previously established. This drawing may not be reproduced, copied or used as the basis for manufacture or sale without written permission.